
ACCENT 12V

5011



LANDSCAPE LIGHTING





Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

Landscape accent luminaire. One fixture replaces all older halogen landscape accent lights

FEATURES

- Adjustable and lockable beam angle
- Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- · Includes a detachable shroud
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Mounting stake, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- MLV dimmable with remote MLV dimmers

ORDERING NUMBER

		Color Temp		Finish	
5011 A	ccent 12V	27 30 40	2700K 3000K 4000K	BK BZ BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass

5011-

Example: 5011-30BBR

SPECIFICATIONS

Input: 9 - 15VAC (Transformer is required)

Power: 1W to 18W / 2VA - 23VA **Brightness:** 50 lm to 1090 lm

Beam Angle: 10° to 60° CRI: 85

Rated Life: 70,000 hours

ACCENT 12V

5011



Accessories				
Accent Snoot	5010-SNOOT-BK 5010-SNOOT-BZ 5010-SNOOT-BBR	Black on Alum Bronze on Alur Bronze on Bras	minum	Shields lamp and reduces glare
6" Long Shroud	5010-LSHR-BK 5010-LSHR-BZ 5010-LSHR-BBR	Black on Alum Bronze on Alur Bronze on Bras	minum	Reduce glare. Ideal for downlighting application
Additional Stake	9000-ST9-BZ	Bronze		Durable PVC stake
Surface Mount Flange/Stake	5000-SCP-BZ5000-SCP-BBR5000-SCP-BK	Bronze on Alun Bronze on Bras Black on Alumi	S	Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box
Guardian Mount	9000-SP9-BZ	Stainless Steel		Heavy duty stainless steel spike to position fixture Formed from a single piece of metal
Gutter Mount Bracket	5000-GM-BK	Stainless Steel		Stainless Steel universal mounting bracket for gutter mounting fixture
Tree Mount Junction Box	5000-TCP-BZ 5000-TCP-BK	Bronze on Alur Black on Alum		Bronze on Aluminum box with Stainless steel mounting screws. Two ½" NPT threaded holes
Optics	LENS-20-AMB Ami LENS-20-GRN Gree LENS-20-RED Red	en LENS-20-FR	Frosted	Enhances saturation of florals and foliage
Extension Rods	5000-X04-BZ 4 in 5000-X04-BK 4 in 5000-X08-BZ 8 in 5000-X08-BK 8 in 5000-X12-BZ 12 in 5000-X12-BK 12 in		18 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler	5000-LCO-BZ	Bronze		

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS *150W Max*

9300-TRN-SS *300W Max*

9600-TRN-SS 600W Max

