


# ACCENT 12V

5011

# WAC

## LANDSCAPE LIGHTING



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

Landscape accent luminaire. One fixture replaces all older halogen landscape accent lights

### FEATURES

- Adjustable and lockable beam angle
- Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- Includes a detachable shroud
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Mounting stake, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- MLV dimmable with remote MLV dimmers

### SPECIFICATIONS

- Input:** 9 - 15VAC (Transformer is required)
- Power:** 1W to 18W / 2VA - 23VA
- Brightness:** 50 lm to 1090 lm
- Beam Angle:** 10° to 60°
- CRI:** 85
- Rated Life:** 70,000 hours

### ORDERING NUMBER

		Color Temp	Finish
<b>5011</b>	<i>Accent 12V</i>	<b>27</b> 2700K	<b>BK</b> <i>Black on Aluminum</i>
		<b>30</b> 3000K	<b>BZ</b> <i>Bronze on Aluminum</i>
		<b>40</b> 4000K	<b>BBR</b> <i>Bronze on Brass</i>

**5011-**\_\_\_\_\_

Example: **5011-30BBR**

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760











# ACCENT 12V

5011

# WAC

## LANDSCAPE LIGHTING

### Accessories

Accent Snoot		<b>5010-SNOOT-BK</b> <b>5010-SNOOT-BZ</b> <b>5010-SNOOT-BBR</b>	Black on Aluminum Bronze on Aluminum Bronze on Brass	Shields lamp and reduces glare	
6" Long Shroud		<b>5010-LSHR-BK</b> <b>5010-LSHR-BZ</b> <b>5010-LSHR-BBR</b>	Black on Aluminum Bronze on Aluminum Bronze on Brass	Reduce glare. Ideal for downlighting application	
Additional Stake		<b>9000-ST9-BZ</b>	Bronze	Durable PVC stake	
Surface Mount Flange/Stake		<b>5000-SCP-BZ</b> <b>5000-SCP-BBR</b> <b>5000-SCP-BK</b>	Bronze on Aluminum Bronze on Brass Black on Aluminum	Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box	
Guardian Mount		<b>9000-SP9-BZ</b>	Stainless Steel	Heavy duty stainless steel spike to position fixture Formed from a single piece of metal	
Gutter Mount Bracket		<b>5000-GM-BK</b>	Stainless Steel	Stainless Steel universal mounting bracket for gutter mounting fixture	
Tree Mount Junction Box		<b>5000-TCP-BZ</b> <b>5000-TCP-BK</b>	Bronze on Aluminum Black on Aluminum	Bronze on Aluminum box with Stainless steel mounting screws. Two 1/2" NPT threaded holes	
Optics		<b>LENS-20-AMB</b> <b>LENS-20-GRN</b> <b>LENS-20-RED</b>	Amber Green Red	<b>LENS-20-BLU</b> Blue <b>LENS-20-FR</b> Frosted <b>LENS-20-SPR</b> Spread	Enhances saturation of florals and foliage
Extension Rods		<b>5000-X04-BZ</b> 4 in <b>5000-X04-BK</b> 4 in <b>5000-X08-BZ</b> 8 in <b>5000-X08-BK</b> 8 in <b>5000-X12-BZ</b> 12 in <b>5000-X12-BK</b> 12 in		<b>5000-X18-BZ</b> 18 in <b>5000-X18-BK</b> 18 in <b>5000-X24-BZ</b> 24 in <b>5000-X24-BK</b> 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler		<b>5000-LCO-BZ</b>	Bronze		

### Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed  
See transformer spec sheet for details and its accessories

**9075-TRN-SS**  
75W Max

**9150-TRN-SS**  
150W Max

**9300-TRN-SS**  
300W Max

**9600-TRN-SS**  
600W Max



wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760