

Step Light with Photocell

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Voltage	Color Temp & CRI	Lumens	Finish
WL-LED202 120 VAC	3000K 90 Amber	65 65	BK Black on Aluminum BN Brush Nickel on Aluminum BZ Bronze on Aluminum SS Stainless Steel WT White on Aluminum

Example: WL-LED202-30-BK

FEATURES

- Options in die-cast brass or 316 marine-grade stainless steel
- Fits into 2"×4" J-Box with minimum inside dimensions of 3"×2"×2"
- · No driver needed
- No heat radiation
- Low profile, flush to wall aesthetics with no visible hardware
- Balanced lighting, free of shadows with minimum glare
- Integrated photocell for energy saving
- Driver concealed within the fixture
- 5 Year warranty

SPECIFICATIONS

Construction: Corrosion resistant aluminum alloy, Stainless Steel

Power: 2W

Input: 120 VAC, 50/60Hz
Light Source: Integrated LED

3 Step Mac Adam Ellipse

Lens: Tempered Glass
Rated Life: 54000 Hours

Finish: Enamel Coated:Black on Aluminum, Enamel

Coated::Brush Nickel on Aluminum, Enamel

Coated:::Bronze on Aluminum, Enamel Coated::::Stainless

Steel, Enamel Coated:::::White on Aluminum

Operating Temp: $-40^{\circ}\text{F to } 122^{\circ}\text{F } (-40^{\circ}\text{C to } 50^{\circ}\text{C})$

Standards: ETL, cETL, Wet Location Listed, IP66, ADA



FINISHES:



LINE DRAWING:

