


PRODUCT CODE: EC322WHM-A13-BB-GU-4

LED METAL RUNNING MAN EXIT SIGN AND EMERGENCY LIGHT COMBO



HOUSING/MOUNTING

The new Etlin-Daniels EC322WHM-A13-BB-GU-4 LED Running Man Combo Exit Sign is constructed with a durable and compact steel housing and is a compliment to many application decors.

The sign components and universal canopy snap together for simple side and wall mount applications, and the 2W thermoplastic combo heads are fully adjustable to provide maximum emergency illumination. 3 Running Man pictogram legends are supplied to cover all directional orientations on both single and double sided installations. Wall mounting is achieved using the spider knockout pattern. LED's operate in AC mode and emergency DC mode.


FEATURES

- Compact steel LED Running Man Combo Exit Sign
- 3 pictogram legends for directional orientation
- Single & double sided // wall and side mount
- 120-347V AC operation
- Ultrabright LED panel for emergency mode
- 2 x 2W fully adjustable heads
- Test switch and charge indicator
- Built-in 3.6V, 1800mAh Nicad battery for minimum 120 minutes emergency operation
- 24 hour recharge time
- Suitable for damp locations
- CSA Certified
- 3 year limited warranty

PRODUCT SPECIFICATIONS (OPTICAL & ELECTRICAL DATA)

LED TYPE	LED QTY	VOLTAGE	POWER FREQUENCY	POWER FACTOR
5 LED ROUND	10 PCS	120V-347V	50/60HZ	120V - .90 347V - .90

PRODUCT SPECIFICATIONS

WATTAGE	FIXTURE MATERIAL	LIFE SPAN	STORAGE TEMP	OPERATING TEMP	PRODUCT DIMENSIONS	CARTON SIZE	
2.6W-120V 3.5W-277V 4.2W-347V	METAL STEEL	>50,000 HOURS	-10°C~+40°C -14°F~+104°F	-5°C~+30°C -32°F~+104°F	12.20 X 2.91 X 7.55 INCHES (310 X 74 X 192 MM)	12.60 X 3.54 X 11.02 INCHES (320 X 90 X 280 MM)	

ADDITIONAL INFORMATION

INSTALLATION METHOD	FIXTURE COLOR	OPERATION TYPE
WALL MOUNT	WHITE METAL CONSTRUCTION	LED CIRCUITS IN NORMAL (AC INPUT) AND EMERGENCY (DC INPUT) MODES / DIRECTIONAL LED HEADS OPERATION IN DC MODE


CATALOG #		TYPE
PROJECT		DATE
PREPARED BY		

PRODUCT CODE: EC322WHM-A13-BB-GU-4


LED METAL RUNNING MAN EXIT SIGN AND EMERGENCY LIGHT COMBO

LUMINAIRE PHOTOMETRIC (TEST REPORT)

ILLUMINANCE (AT A DISTANCE) -

13.12FT 4M	4.94, 10.56FC 53.14, 113.71LX		1.90FT 0.58CM	
16.40FT 5M	3.16, 6.76FC 34.01, 72.77LX		1.90FT 0.58CM	
19.69FT 6M	2.19, 4.69FC 23.62, 50.54LX		2.85FT 0.87CM	
22.97FT 7M	1.61, 3.45FC 17.35, 37.13LX		2.85FT 0.87CM	
26.25FT 8M	1.23, 2.64FC 13.28, 28.34LX		3.81FT 1.17CM	
29.53FT 9M	0.98, 2.09FC 10.50, 22.46LX		4.28FT 1.30CM	
32.81FT 10M	0.79, 1.69FC 8.50, 18.19LX		4.28FT 1.30CM	
36.09FT 11M	0.65, 1.40FC 7.03, 15.04LX		4.28FT 1.30CM	
39.37FT 12M	0.55, 1.17FC 5.90, 12.63LX		5.71FT 1.74CM	
49.21FT 15M	0.35, 0.75FC 3.78, 8.09LX		7.14FT 2.17CM	
HT	EAVG/EMAX		ANGLE: 8.3DEG	DIA

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



CERTIFICATIONS



ACCESSORIES

**REPLACEMENT BATTERY
NCB-3.6V-1800**

ORDERING INFORMATION - EC SERIES

SERIES	MODEL	COLOR	INPUT VOLTAGE	VOLTAGE	BATTERY	FACE COLOR	MOUNTING	WATTAGE
E.G. EC	322	WHM	A	13	BB	G	U	4
EC - EXIT / LIGHT COMBO	322 - MODEL	WH - WHITE METAL	A - AC	13 - 120-347V	BB - BATTERY BACKUP	G - GREEN	U - UNIVERSAL	2 X 2W

Head Office - 1850 Wilson Ave. · Toronto, ON · M9M 1A1 · Tel: 416.741.7336 · Fax: 416.741.9104

Toll Free: in Canada. 1.800.661.9610 · in USA. 1.888.762.5384 (SOCKETS4U)

www.etlin-daniels.com · For sales/service questions - sales@etlin.com