

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Hardscape

Quick Connect Luminaire With Dual CCT

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
○ 7062 6"	○ 27/30 2700K/3000K - 85	4.5W	110	○ BBR Bronze on Brass
○ 7122 12"	○ 27/30 2700K/3000K - 85	7.0W	230	○ BZ Bronze on Aluminum
○ 7182 18"	○ 27/30 2700K/3000K - 85	8.5W	350	○ GH Graphite on Aluminum
				○ SD Sand on Aluminum

Example: **7062-27/30BBR**

DESCRIPTION

Integral brightness control, select color temperature option. Hardscape easily detaches from capstone bracket after installation. Factory sealed water-tight fixture. Tightly spaced and diffused LEDs for even illumination. Mounting options included: stainless steel under capstone brackets, clips and hardware. Can be mounted on wall in all orientations

FEATURES

- Quick release connection at fixture to easily detach after installation
- Integral brightness control, select color temperature option
- Hardscape easily detaches from capstone bracket after installation
- Transformer required
- 10 yrs warranty

SPECIFICATIONS

Construction:	Corrosion resistant aluminum alloy, Solid die-cast brass
Power:	8.5W, 7.0W, 4.5W
Input:	50/60Hz, 9-15 VAC
Dimming:	Integral Brightness Control
Light Source:	Integrated LED
	3 Step Mac Adam Ellipse
Lens:	PC Diffuser
Rated Life:	50000 Hours
Mounting:	Can be mounted on wall in all orientations
Finish:	Enamel Coated Bronze on Aluminum, Enamel Coated Bronze on Brass, Enamel Coated Sand on Aluminum, Enamel Coated Graphite on Aluminum
Operating Temp:	-40°F to 122°F (-40°C to 50°C)
Standards:	ETL, cETL, Wet Location Listed, IP66



FINISHES



LINE DRAWING

