GRAND ACCENT 12V

5211



LANDSCAPE LIGHTING



PRODUCT DESCRIPTION

Landscape accent luminaire. One fixture replaces all older halogen landscape accent lights

FEATURES

- Adjustable and lockable beam angle
- Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- Includes a detachable shroud
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Mounting stake, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- Not suitable to use with external dimmers

ORDERING NUMBER

	Color Te	emp F	Finish	
5211 Grand 12V	Accent 30	3000K -		Black on Aluminum Bronze on Aluminum

5211-____

Example: 5211-40BK

SPECIFICATIONS

Input: 9 - 15VAC (Transformer is required)

Power: 15W to 35W / 21VA - 44VA **Brightness:** 740 lm to 2000 lm

Beam Angle: 15° to 60° CRI: 85

Rated Life: 45,000 hours

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

GRAND ACCENT 12V

5211



Accessories					
Accent Snoot	5211-SNOOT-BK 5211-SNOOT-BZ		Black on Aluminum Bronze on Aluminum		Shields lamp and reduces glare
6"Long Shroud	5211-LSHR-BK 5211-LSHR-BZ		Black on Aluminum Bronze on Aluminum		Reduce glare. Ideal for downlighting application
Additional Stake	9000-ST9-BZ		Bronze		Durable PVC stake
Surface Mount Flange/Stake	5000-SCP-BZ 5000-SCP-BBR 5000-SCP-BK		Bronze on Aluminum Bronze on Brass Black on Aluminum		Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box
Guardian Mount	9000-SP9-BZ		Stainless Steel		Heavy duty stainless steel spike to position fixture Formed from a single piece of metal
Gutter Mount Bracket	5000-GM-BZ 5000-GM-BK		Stainless Steel		Stainless Steel universal mounting bracket for gutter mounting fixture
Tree Mount Junction Box	5000-TCP-BZ 5000-TCP-BK		Bronze on Aluminum Black on Aluminum		Bronze on Aluminum box with Stainless steel mounting screws. Two $\frac{1}{2}$ " NPT threaded holes
Optics	LENS-25-AMB LENS-25-GRN LENS-25-RED	Amber Green Red	LENS-25-BLU LENS-25-FR	Blue Frosted	Enhances saturation of florals and foliage
Extension Rods	5000-X04-BZ 5000-X04-BK 5000-X08-BZ 5000-X08-BK 5000-X12-BZ 5000-X12-BK	4 in 4 in 8 in 8 in 12 in 12 in	5000-X18-BZ 5000-X18-BK 5000-X24-BZ 5000-X24-BK	18 in 18 in 24 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler	5000-LCO-BZ		Bronze		

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS *150W Max*

9300-TRN-SS 300W Max

9600-TRN-SS 600W Max

