


solar attribute list



| |  |  |  |  |  |  |  |  |
|------------------------------------|---|---|---|---|---|---|---|---|
| | RP-SWL | RP-SSL | RP-SML | RP-SPT | RP-SDL | RP-SBL | RP-SFL | RP-SAL |
| Motion Sensor | Yes | No | Yes | Yes | No | No | No | Yes |
| Photocell | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| # of modes | 3 | 1 | 3 | 2 | 1 | 1 | 1 | 7 |
| Battery | LiFePO4 | Li-Ion | Li-Ion | Li-Ion | Li-Ion | LiFePO4 | Li-Ion | LiFePO4 |
| # of Cycles | 2000 | 1500 | 1500 | 1500 | 1500 | 2000 | 1500 | 2000 |
| Remote | Included, Optional | No | No | No | No | No | No | Included, required |
| Solar Panel | Adjustable | Fixed | Fixed | Fixed | Fixed | Fixed | Adjustable | Adjustable |
| Battery Display | No | No | Yes | No | Yes | Yes | Yes | No |
| Warranty (Years) | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 5 |
| CCT | 4K | 4K | 4K | 4K | 4K | 4K | 4K | 5K |
| Operating/ Discharging Temp | 5°F - 113°F | -13°F - 149°F | -13°F - 149°F | -4°F - 149°F | -4°F - 140°F | -13°F - 140°F | -4°F - 140°F | -4°F - 122°F. |
| Charging Temperature | 32°F - 113°F | 32°F - 149°F | 32°F - 149°F | 32°F - 149°F | 32°F - 113°F | 32°F - 149°F | 32°F - 113°F | 32°F - 149°F |
| Replaceable Battery | Yes | No | No | Yes | Yes | Yes | Yes | Yes |
| Initial Power-Up Location | Remote | On Fixture | On Fixture | On Fixture | On Fixture | On Fixture | On Fixture | Remote |