# **3" INGROUND 120V**

5032



## LANDSCAPE LIGHTING







Fixture Type:	
Catalog Number:	
Project:	
Location:	

### PRODUCT DESCRIPTION

Landscape Wall Wash luminaire

### **FEATURES**

- Adjustable beam angle
- Integral dimmer
- IP67 rated, protected from temporary immersion under water
- Drive over up to 4500lbs
- Solid diecast brass or corrosion resistant aluminum
- Available concrete pour kit
- 6' lead wire and wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1598 listed for indoor and outdoor use
- Not suitable to use with external dimmers

#### **SPECIFICATIONS**

 Input:
 110V - 120VAC

 Power:
 3W to 11.5W

 Brightness:
 65 lm to 515 lm

 Beam Angle:
 15° to 60°

 CRI:
 85

 Rated Life:
 45,000 hours

IEC safety Standard	Walk over	Drive over	
Resistance to static load test	Yes (1125lbs)	Yes (4496lbs)	
Resistance to torque and shear loads test	N/A	Yes	

#### **ORDERING NUMBER**

		Color Temp		Finish	
5032	3" Inground 120V	30	3000K	BZ BBR	Bronze on Aluminum Bronze on Brass


**Module Replacement** 

3000K **M5032LE-30BZ** 



5032-30

Example: **5032-30BBR** 







Adjust Beam Angles

Presets at

15°, 30°, 45°, 60°



Adjustable WAC Inground
Adjust the light to where you need it









**Rock Guard** 

Protects the fixture face



**5030-GRD-BZ**Bronze on Aluminum

**5030-GRD-BBR** *Bronze on Brass* 

Optics

Enhances saturation of florals and foliage



**LENS-25-AMB** *Amber* 

**LENS-25-RED** *Red* 

LENS-25-FR

Frosted

LENS-25-GRN Green **LENS-25-BLU** *Blue* 

**LENS-25-HCL** Honeycomb Louver

Reduces glare

Concrete Pour Kit

For installation in concrete Five ½" NPT threaded holes, PC

5030-PIP-PVC

Shown with temporary dense foam cap



