

BFS

BULLET FLOODLIGHT (1/2" Knuckle Mount)

PROJECT:		
SCHEDULE:	DATE:	
PREPARE BY:		
NOTES:		

DESCRIPTION

naturaLED® Bullet Flood light (BFS) delivers exceptional illumination performance to landscape and security lighting. Our Bullet Flood light provides beam angle distribution of 40°, rated IP65, and comes with 1/2" NPT knuckle mount. Creating bright, security and spot lighting for a variety of applications such as perimeter, entryway, facades, landscapes, retail and residential complexes and architectural lighting.



Rated Life 50,000 Hours Warranty 5 Years

APPLICATIONS

Security, Architectural, Perimeter, Entryway, Pathway, Landscape

FEATURES

- DLC Standard
- IP65 Rated
- ETL Listed
- Long life LED chips
- ColorTemp: 3000K, 5000K
- Beam Angle: 40°
- Input line voltage: 120-277V
- CRI: 80
- Powerfactor > 0.9
- 1/2" NPT threaded knuckle mount
- Material: Aluminum die-cast housing
- Voltage Frequency (Hz): 50/60
- Operating temperature: -22°F 122°F
- 5 Year Warranty
- Finish Color: Bronze

SAMPLE NUMBER LED-FXBFS10/40/830/BZ-KNC								
STYLE	FAMILY	SERIES	WATTAGE	BEAM ANGLE	COLOR TEMP	COLOR	ACCESSORY	
LED	FX	BFS	10	40	830	BZ	KNC	
led lighting	fixture	bullet floodlight	10 watt	40 deg	CRI 80 3000K	Bronze	1/2" knuckle	



















*P= Premium DLC / *S = Standard DLC


ORDERING


Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Equiv. Wattage (W)	Knuckle	IP65 Rated	DLC (S/P)
10	9291	LED-FXBFS10/40/830/BZ-KNC	3000K	1,137	75	1/2"	•	S
10	9292	LED-FXBFS10/40/850/BZ-KNC	5000K	1,167	75	1/2"	•	S
21	9293	LED-FXBFS20/40/830/BZ-KNC	3000K	2,291	150	1/2"	•	S
21	9294	LED-FXBFS20/40/850/BZ-KNC	5000K	2,373	150	1/2"	•	S

DIMENSIONS

10W / 21W


1.39-lbs






PHOTOMETRICS CHART

10 Watt DLC Standard





21 Watt DLC Standard





PACKAGE

Case Oty 10 pcs

