

FMM FLUSH MOUNT MODERN (CCT5)

DESCRIPTION

naturaLED® Flush Mount Modern (FMM) Features a white acrylic diffuser with a sleek, compact design. This energy-efficient LED solution will provide up to 86% energy savings over incandescent lighting. FMM series ceiling lights are perfect for kitchens, open areas, hallways, bedrooms, or other decorative lighting. FMM mounts flush to the ceiling or wall, it is suitable for residential or commercial applications. This design features a low-profile body with nickel finish accents and a white acrylic diffuser. Available in three sizes, replacing up to 200W incandescent, and 5 selectable color temperatures.

APPLICATIONS

Kitchen, Decoration, Hallway, Bedroom, Hospitality, Ceiling Mount Lighting

FEATURES

- Energy Star
- Damp Location
- ETL Listed
- Uniform light distribution and consistent color
- Lightweight and easy installation
- Retrofit for Incandescent and CFL flush mount
- Color Temperature Selectable: 2700K, 3000K, 3500K, 4000K, 5000K
- Input line voltage: 120V
- CRI: 90
- Powerfactor >0.9
- Dimmable
- Operating temperature: 5°F - 104°F
- Recommended ceiling height: 8-10ft
- 5Year Warranty
- Material: Aluminum housing & white acrylic

PROJECT:

SCHEDULE:

DATE:

PREPARE BY:

NOTES:



SAMPLE NUMBER LED12FMM-126L9CCT5-NI

STYLE	DIAMETER	SERIES	LUMEN	CRI	COLOR TEMP	COLOR
LED led lighting	12 12 inch	FMM flush mount modern	126L 1,260 lumens	9 CRI 90	CCT5 2700K 3000K 3500K 4000K 5000K	NI nickel



FLUSH MOUNT MODERN CCT5


CEILING & AREA LUMINAIRES

ORDERING


Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Equiv. Wattage (W)	Size	Damp Location	Energy Star
18	9356	LED12FMM-126L9CCT5-NI	27/30/35/40/50K	1,260	120	12"	•	•
24	9357	LED14FMM-180L9CCT5-NI	27/30/35/40/50K	1,800	150	14"	•	•
24	9358	LED16FMM-190L9CCT5-NI	27/30/35/40/50K	1,900	200	16"	•	•

DIMENSIONS


18W (12-inch)
1.72-lbs



24W (14-inch)
2.49-lbs




24W (16-inch)
3.01-lbs



PHOTOMETRICS CHART


18W (12-inch)
Energy Star



Center Beam fc	Beam Width
1.3R	237 fc 3.8 ft 3.9 ft
2.7R	55.1 fc 7.9 ft 8.1 ft
4.0R	25.1 fc 11.8 ft 12.0 ft
5.3R	14.3 fc 15.6 ft 15.8 ft
6.7R	8.94 fc 19.7 ft 20.0 ft
8.0R	6.27 fc 23.5 ft 23.9 ft

■ Vert. Spread: 111.6°
■ Horiz. Spread: 112.4°


24W (14-inch)
Energy Star



Center Beam fc	Beam Width
1.3R	328 fc 4.0 ft 4.0 ft
2.7R	76.1 fc 8.3 ft 8.3 ft
4.0R	34.7 fc 12.2 ft 12.2 ft
5.3R	19.7 fc 16.2 ft 16.2 ft
6.7R	12.4 fc 20.5 ft 20.5 ft
8.0R	8.67 fc 24.5 ft 24.5 ft

■ Vert. Spread: 113.7°
■ Horiz. Spread: 113.6°

24W (16-inch)
Energy Star



Center Beam fc	Beam Width
1.3R	347 fc 4.3 ft 4.3 ft
2.7R	80.4 fc 8.9 ft 9.0 ft
4.0R	36.6 fc 13.2 ft 13.3 ft
5.3R	20.9 fc 17.5 ft 17.6 ft
6.7R	13.0 fc 22.2 ft 22.3 ft
8.0R	9.15 fc 26.5 ft 26.6 ft

■ Vert. Spread: 117.9°
■ Horiz. Spread: 117.9°

PACKAGE

Case Qty
2 pcs

