

## Tamper-Resistant USB-CHARGER & DUPLEX RECEPTACLE

### Product Features

- Good heat dissipation  
Design of bottom grid, good cooling
- Super high impact resistance and thermal stability  
Cover pans are made of high quality polycarbonate
- Chemical corrosion resistance  
Fingerprint-resistant zinc plated mounting brackets
- Security  
Security doors designed to prevent people accidental exposure
- Mechanical life  
Unloaded plug ≥ 5000Sec
- UL498 UL943 CSA-C22.2 No.42 USB1.0/2.0/3.0
- Housing material flame retardant grades UL94-V2
- Rated working current: 15A / 20A
- Rated working voltage: 125V
- Power Frequency: 60HZ
- USB Voltage & Current: 5VDC 4.8A
- Wire Specifications: #14- #10AWG
- Electric strength: Pressure resistance 1500V 50Hz Duration 1 Min
- Working Temperature: -20°C~60°C
- Insulation resistance: >50MΩ (DC500V)



If the devices combined power requirements exceed the power capacity of the USB Ports, the charger will automatically shut down to protect your devices.

## Tamper-Resistant USB-CHARGER & DUPLEX RECEPTACLE

### Product Features

- Good heat dissipation  
Design of bottom grid, good cooling
- Super high impact resistance and thermal stability  
Cover pans are made of high quality polycarbonate
- Chemical corrosion resistance  
Fingerprint-resistant zinc plated mounting brackets
- Security  
Security doors designed to prevent people accidental exposure
- Mechanical life  
Unloaded plug ≥ 5000Sec
- UL498 UL943 CSA-C22.2 No.42 USB1.0/2.0/3.0
- Housing material flame retardant grades UL94-V2
- Rated working current: 15A
- Rated working voltage: 125V
- Power Frequency: 60HZ
- USB Voltage & Current: 5VDC 4.8A
- Wire Specifications: #14- #10AWG
- Electric strength: Pressure resistance 1500V 50Hz Duration 1 Min
- Working Temperature: -20°C~60°C
- Insulation resistance: >50MΩ (DC500V)

