



# MSC40 Series

## 200 AMP - MULTI POSITION STUD TYPE 400 Amp Main c/w Blank Compartment

CATALOGUE #	TYPE	DESCRIPTION	DIMENSIONS (IN.)			WEIGHT
			H	W	D	
<b>MSC42TW</b>	U/G	2 gang, c/w 1/2" Compression studs	22 <sup>13</sup> / <sub>16</sub>	27 <sup>13</sup> / <sub>16</sub>	6 <sup>1</sup> / <sub>8</sub>	48 lbs.
<b>MSC43TW</b>	U/G	3 gang, c/w 1/2" Compression studs	22 <sup>13</sup> / <sub>16</sub>	37 <sup>1</sup> / <sub>16</sub>	6 <sup>1</sup> / <sub>8</sub>	65 lbs.
<b>MSC44TW</b>	U/G	4 gang, c/w 1/2" Compression studs	22 <sup>13</sup> / <sub>16</sub>	46 <sup>5</sup> / <sub>16</sub>	6 <sup>1</sup> / <sub>8</sub>	83 lbs.
<b>MSC45TW</b>	U/G	5 gang, c/w 1/2" Compression studs	22 <sup>13</sup> / <sub>16</sub>	55 <sup>9</sup> / <sub>16</sub>	6 <sup>1</sup> / <sub>8</sub>	103 lbs.
<b>MSC46TW</b>	U/G	6 gang, c/w 1/2" Compression studs	22 <sup>13</sup> / <sub>16</sub>	64 <sup>13</sup> / <sub>16</sub>	6 <sup>1</sup> / <sub>8</sub>	121 lbs.

\* Also available with two (2) blank compartments (see MSC800 Series)

- Factory Bussed 400 Amp Mains
- 200 Amp, 600 VOLT per position
- 2 - 6 position horizontal
- 4 Jaw meter sockets
- CSA weatherproof enclosure 3R
- Approved conductor range:  
Line - studs (1/2" per phase) provided for compression type wire connectors  
Load - #6 - 250 MCM CU/AL
- Underground only

- Use **SXK503** for 5th jaw at 9 O'clock
- Add suffix "H" for right hand entry

KNOCKOUT CODE	CONDUIT SIZE
<b>G</b>	1 <sup>1</sup> / <sub>4</sub> ", 1 <sup>1</sup> / <sub>2</sub> ", 2", 2 <sup>1</sup> / <sub>2</sub> "
<b>S</b>	3", 3 <sup>1</sup> / <sub>2</sub> ", 4"
<b>AA</b>	1/2"

