



# SE Series

## 100 AMP - 600 VOLTS King Size

| CATALOGUE # | TYPE      | DESCRIPTION   | DIMENSIONS (IN.)                 |                               |                               | WEIGHT  |
|-------------|-----------|---|----------------------------------|-------------------------------|-------------------------------|---------|
|             |           |   | H                                | W                             | D                             |         |
| SE400RW     | O/H & U/G | 4 Jaw   | 13 <sup>11</sup> / <sub>16</sub> | 7 <sup>5</sup> / <sub>8</sub> | 4 <sup>5</sup> / <sub>8</sub> | 8 lbs.  |
| SE400PW     | O/H       | 4 Jaw c/w hub opening, hub plate not included                         | 13 <sup>11</sup> / <sub>16</sub> | 7 <sup>5</sup> / <sub>8</sub> | 4 <sup>5</sup> / <sub>8</sub> | 8 lbs.  |
| SE400JW     | O/H       | 4 Jaw c/w 1 <sup>1</sup> / <sub>4</sub> " hub                         | 13 <sup>11</sup> / <sub>16</sub> | 7 <sup>5</sup> / <sub>8</sub> | 4 <sup>5</sup> / <sub>8</sub> | 8 lbs.  |
| SE400BW     | O/H       | 4 Jaw - twin hub opening c/w two 1 <sup>1</sup> / <sub>4</sub> " hubs | 13 <sup>11</sup> / <sub>16</sub> | 7 <sup>5</sup> / <sub>8</sub> | 4 <sup>5</sup> / <sub>8</sub> | 8 lbs.  |
| SE400BP     | O/H       | 4 Jaw - twin hub opening c/w closure plates                           | 13 <sup>11</sup> / <sub>16</sub> | 7 <sup>5</sup> / <sub>8</sub> | 4 <sup>5</sup> / <sub>8</sub> | 8 lbs.  |
| SE400TW     | U/G       | 4 Jaw - blank top   | 13 <sup>11</sup> / <sub>16</sub> | 7 <sup>5</sup> / <sub>8</sub> | 4 <sup>5</sup> / <sub>8</sub> | 8 lbs.. |
| SE405RW     | O/H & U/G | 5 Jaw - 5th Jaw at 9 O'clock  | 13 <sup>11</sup> / <sub>16</sub> | 7 <sup>5</sup> / <sub>8</sub> | 4 <sup>5</sup> / <sub>8</sub> | 8 lbs.  |
| SE420RW     | O/H & U/G | 4 Jaw - c/w water heater lugs   | 13 <sup>11</sup> / <sub>16</sub> | 7 <sup>5</sup> / <sub>8</sub> | 4 <sup>5</sup> / <sub>8</sub> | 8 lbs.  |

- Conductor range No. 6 - 1/0 AWG CU/AL
- CSA weatherproof enclosure 3R
- Approved for copper or aluminum
- For extra ground lug on neutral add suffix NB - Used in New Brunswick

- Field adaptable accessories
- 5th Jaw at 9 O'clock - **SXK503**
- Insulated neutral - **INK100**
- 5th Jaw at 6 O'clock - **INK105Y**



| KNOCKOUT CODE | CONDUIT SIZE   |
|---------------|--|
| AA            | 1/2"   |
| D             | 1 <sup>1</sup> / <sub>4</sub> ", 1 <sup>1</sup> / <sub>2</sub> ", 2"     |
| E             | 1", 1 <sup>1</sup> / <sub>4</sub> ", 1 <sup>1</sup> / <sub>2</sub> ", 2" |

