



# JA Series

## 200 AMP SOCKET & BREAKER

### Single Phase, Splitter, comb. without breaker

CATALOGUE #	TYPE	DESCRIPTION	DIMENSIONS (IN.)			WEIGHT
			H	W	D	
JA4124E	O/H	4 Jaw , Provision for field-installed Cutler Hammer 200A 2 Pole 10kA rated circuit breaker, provision for Pole Mounting	36 <sup>5</sup> / <sub>16</sub>	12	5 <sup>1</sup> / <sub>4</sub>	38 lbs.
JA4124E-T	U/G	4 Jaw , Provision for field-installed Cutler Hammer 200A 2 Pole 10kA rated circuit breaker, c/w Pole Mounting Brackets	36 <sup>5</sup> / <sub>16</sub>	12	6	38 lbs.
JA4124EF	O/H & U/G	4 Jaw , Provision for field-installed Cutler Hammer 200A 2 Pole 10kA rated circuit breaker, c/w Pole Mounting Brackets	36 <sup>5</sup> / <sub>16</sub>	12	5 <sup>1</sup> / <sub>4</sub>	39 lbs.

- 200 Amp - 120/240 VOLT
- Combination meter socket & circuit breaker
- CSA enclosure 3R
- Conductor range #6 - 250 MCM CU/AL
- Cutler Hammer breaker to be field installed

KNOCKOUT CODE	CONDUIT SIZE
H	1 <sup>1</sup> / <sub>4</sub> "
J	1 <sup>1</sup> / <sub>4</sub> ", 1 <sup>1</sup> / <sub>2</sub> "
L	1 <sup>1</sup> / <sub>2</sub> "
M	1 <sup>1</sup> / <sub>2</sub> ", 2"

