



# EK Series

## 200 AMP - 600 VOLTS Oversize Enclosure

CATALOGUE #	TYPE	DESCRIPTION	KO TYPE	DIMENSIONS (IN.)			WEIGHT
				H	W	D	
<b>EK400RO</b>	O/H & U/G	4 Jaw, oversize enclosure	F	18	12	4 <sup>3</sup> / <sub>4</sub>	15 lbs.
<b>E400RO</b>	O/H & U/G	4 Jaw, straight lugs on line side	F	18	12	4 <sup>3</sup> / <sub>4</sub>	15 lbs.
<b>EK400TO</b>	U/G	4 Jaw, underground oversize enclosure	F	18	12	4 <sup>3</sup> / <sub>4</sub>	15 lbs.
<b>EK400ROBC</b>	O/H & U/G	4 Jaw, c/w 3" KO in bottom	E	18	12	5 <sup>1</sup> / <sub>8</sub>	15 lbs.
<b>EK200XL</b>	O/H & U/G	4 Jaw, 350MCM type connectors on line side	E	22 <sup>1</sup> / <sub>4</sub>	16 <sup>1</sup> / <sub>2</sub>	4 <sup>3</sup> / <sub>4</sub>	22 lbs.
<b>EK200XLD</b>	O/H & U/G	4 Jaw, 350MCM type connectors on line side, 4-1/2" in top hub opening	E	22 <sup>1</sup> / <sub>4</sub>	16 <sup>1</sup> / <sub>2</sub>	4 <sup>3</sup> / <sub>4</sub>	22 lbs.

- CSA enclosure 3R
- Barrel type connectors angled at 45°
- Conductor range No. 6 -250 MCM CU/AL
- Lay-in neutral (can be used with unbroken neutral wire)
- Add suffix NS for ground lug on neutral for New Brunswick only

- Field adaptable accessories
- 5th Jaw at 9 O'clock **SXK503**
- 5th Jaw at 6 O'clock **INK501**
- Insulated neutral **INK200**

KNOCKOUT CODE	CONDUIT SIZE
<b>AA</b>	1/2"
<b>G</b>	1 <sup>1</sup> / <sub>4</sub> ", 1 <sup>1</sup> / <sub>2</sub> ", 2", 2 <sup>1</sup> / <sub>2</sub> "
<b>F</b>	1", 1 <sup>1</sup> / <sub>4</sub> ", 1 <sup>1</sup> / <sub>2</sub> ", 2", 2 <sup>1</sup> / <sub>2</sub> ", 3"

