DR40RF-WH/BK/SN

4 inch LED Round Ultra Slim Recessed downlight(Air tight)

Job Information			
Project Name		Туре	
Location			
Quantity		Date	
Contact/ Name			
Notes			

Body

- Durable airtight aluminum
- White polycarbonate diffuser lens for low glare

LED Characteristics

- 12-Watt LED Module
- · Minimal heat emission
- Up to 870 Lumens
- Superior LED Performance and lifespan
- Excellent Color rendering with Spotlight

- Dimming

 10%-100% dimming capability

 Compatible with industry TRIAC/ELV dimmers (contact factory for compatible dimmers list)

Environment

- · Suitable for damp locations
- Suitable for insulated ceiling application
- Can be installed indoor and for outdoor applications

Mounting

- · Included two springs loaded cilps to attach to any ceilling
- The slim profile allow to be mounted under joists or dock work

Description

 DR40RF, a 12watt 4-inch All CCT slim profile round flat LED panel is a high-performance, easy to install downlight. It offers excellent light output, energy efficiency, and streamlined design. Suitable for damp location and use in soffits

Beam Spread

• 110 degree beam spread

LED Driver

- Extruded aluminum junction box with integrated 210mA dimmable driver included
- · Class II electronic LED driver with 100-125V AC input;
- includeds an 12" cable from driver to fixture

Quick Connect Push-in Terminals

• Three "Quick Connect" Push-in terminals for fast and easy

Operating Temperature

• -20 C - 40 C (-4°F - 104°F)





















SPECIFICATION			
Application	Ceiling Recessed Mount	Energy Star	YES
Approved Location	Damp	Input	100-125V AC, 60Hz, 0.09A
Beam Angle	110	LM 79	YES
ССТ	2700K/3000K/3500K/4000K/5000K	LM 80	YES
Certification	cETLus	Lumens	Up to 870
Class II	YES	Lumens per Watt	72.5
Color	White/Black/Brushed Nickel	Power Factor	>0.95
CRI	80+	Projected Life	5 Years
Dimming	YES	Wattage	12 Watt
Dimming Tech	TRIAC/ELV	Cut-Size	4 1/4"









