



Guy Wire

C.S.A. standard guy strand formed from 7 individual strands and hot dip galvanized (4 immersion).

Cat. No.	Diameter	Grade and breaking strength lbs.				Wt.-lbs./ C ft.	Wt.-lbs./ C mtrs.
		50	110	160	180		
14GW	1/4"	1,800	3,950	5,750	6,450	12.9	42.31
516GW	5/16"	3,100	6,800	9,900	11,150	22.2	72.82
38GW	3/8"	3,750	8,250	12,000	13,500	27.0	88.56
716GW	7/16"	5,410	11,900	17,300	19,500	38.8	127.26
12GW	1/2"	7,100	15,600	22,700	25,500	51.0	167.28



Guy Wire

Standard coil and spool sizes carried in stock

Spools:	5,000 feet (1525 meters)	2,500 feet (762.5 meters)
Coils:	500 feet (152.5 meters)	250 feet (76.25 meters)

When ordering, order by Catalogue number length and grade. Please also specify spool or coil.

Prices vary only with diameter and grade, not with the size of spool or coil.

A cutting charge applies to all special size spools and coils.

A deposit charge applies to all spools with less than 2,500 feet of wire.

Aluminum Tie Wire

Cat.No.	Description	Wt./1000 feet
4TWA	# 4 gauge	34 lbs.



4TWA



Guards

STRAIGHT & FLARED

U-Cable Guards

For the protection of rising cable at the lower end of poles. Made from Hot dip galvanized 14 gauge Steel or 1100 grade aluminum to C.S.A. drawing No. G-3, specification C-83.

Made in 2 styles: Straight (UC & UCA) and flared (UCG & UFA). Flared design will fit over underground duct without the need of an adapter. Throat clips (ATC) to round off sharp edges at the top of cable guards are also available.

Cat. No. (steel)	Cat. No. (Aluminum)	L	W	Std.Pkg.	Wt.-lbs./ C (Steel)	Wt.-lbs./ C (Aluminum)
Straight Cable Guards (UC & UCA):						
534UC	534UCA	5'	3/4"	5	330	110
834UC	834UCA	8'	3/4"	5	530	176
5114UC	5114UCA	5'	1-1/4"	5	440	146
8114UC	8114UCA	8'	1-1/4"	5	760	273
5214UC	5214UCA	5'	2-1/4"	5	900	300
8214UC	8214UCA	8'	2-1/4"	5	1300	433
5314UC	5314UCA	5'	3-1/4"	5	1100	366
8314UC	8314UCA	8'	3-1/4"	5	2000	666
5334UC	5334UCA	5'	3-3/4"	3	1500	500
8334UC	8334UCA	8'	3-3/4"	3	2160	720
8414UC	8414UCA	8'	4-1/4"	3	2800	933
55UC	55UCA	5'	5"	3	2250	694
85UC	85UCA	8'	5"	3	3400	914
8514UC	8514UCA	8'	5-1/4"	3	3425	931
86UC	86UCA	8'	6"	3	3400	994
Flared Cable Guards (UCF & UFA):						
5114UCF	5114UFA	5'	1-1/4"	5	460	153
8114UCF	8114UFA	8'	1-1/4"	5	840	280
5214UCF	5214UFA	5'	2-1/4"	5	930	310
8214UCF	8214UFA	8'	2-1/4"	5	1300	443
5314UCF	5314UFA	5'	3-1/4"	5	1540	513
8314UCF	8314UFA	8'	3-1/4"	3	1850	620
8334UCF	8334UFA	8'	3-3/4"	3	2450	816
8414UCF	8414UFA	8'	4-1/4"	3	3010	1029
55UCF	55UCFA	5'	5"	3	2025	812
85UCF	85UFA	8'	5"	3	3200	1100
8514UCF	8514UCFA	8'	5-1/4"	3	3475	1152
86UCF	86UFA	8'	6"	3	3610	1221
11UF	-	29.5"	11.417'	1	3010	N/A

Other sizes available upon request.
Custom flares available upon request.



8214UCF



8214UC



8214UFA



11UF

Guard Straps




STRAPS

Straps

Galvanized and Aluminum

Straps		L	W	Std.Pkg.	Wt.-lbs./ C (Steel)	Wt.-lbs./ C (Aluminum)
Cat.No. (Steel)	Cat.No. (Aluminum)					
Straps (SUC & SCA):						
34SUC	34SCA	3/4 x 1/8	3/4"	200	12	4
114SUC	114SCA	3/4 x 1/8	1-1/4"	200	15	5
214SUC	214SCA	1 x 1/8	2-1/4"	100	24	8
314SUC	314SCA	1 x 3/16	3-1/4"	100	60	20
334SUC	334SCA	1 x 3/16	3-3/4"	50	70	23
414SUC	414SCA	1 x 3/16	4-1/4"	50	80	26
50SUC	50SCA	1 x 3/16	5"	25	90	30
60SUC	60SCA	1 x 3/16	6"	25	100	36

Other sizes available upon request.



Aluminum Throat Clip (ATC)

Cat. No.	Size	Std.Pkg.	Wt.-lbs/ C
114ATC	used on 1 1/4" guard	50	15
214ATC	used on 2 1/4" guard	50	25
314ATC	used on 3 1/4" guard	25	62
334ATC	used on 3 3/4" guard	25	69





Guy Guards

PLASTIC/STEEL

Guy Guards

Made from polyethylene (YG) or 14 gauge galvanized steel (SGG)

Cat.No.	Length	Colour	Std. Pkg.	Wt.-lbs./ C
2YG	2M	Yellow	10	325
7SGG	7'	Galvanized Steel	5	1100



2YG



7SGG



Guy Hooks

34GH made of ductile iron for use with 5/8" or 3/4" bolt. **May be used for down guying attachment. The Guy strand loop may be made on the ground to simplify installation.** The suffix "C" signifies less spurs (for concrete poles).

Cat. No.	Size of Length	Bolt Hole	Std.Pkg.	Wt.-lbs./ C
34GH	6"	13/16	25	118
34GHC (No Spurs)	6"	13/16	25	118
2GH	1.1/2 x 3/8 x 4" 1g	11/16	50	90
Guy Hook Combination -Used with strand or fiberglass strain Insulators				
234GH	6"	13/16	25	130
234GHC	As Above less spurs -Used on concrete poles			



34GH



234GH



2GH



Guy Plates

STRAIN PLATES

Strain Plates (curved)

To prevent pole cutting by guy or messenger.

Cat.No.	Dimension	Gauge	Std.Pkg.	Wt.-lbs./ C
1448SP	4 x 8	14	50	80
10611SP	6 x 11	10	25	100

Additional sizes available upon request.

