

H40 Series

200 AMP - MULTI POSITION 400 Amp Mains



CATALOGUE #	DESCRIPTION	METER POSITIONS	ENCLOSURE SIZE A X B X C	WEIGHT
H42R	2 gang, 400 Amp main, 200 Amp per position	2	22 ³ / ₄ " x 6 ¹ / ₄ " x 18 ⁵ / ₈ "	42 lbs.
H43R	3 gang, 400 Amp main, 200 Amp per position	3	22 ³ / ₄ " x 6 ¹ / ₄ " x 28"	58 lbs.
H44R	4 gang, 400 Amp main, 200 Amp per position	4	22 ³ / ₄ " x 6 ¹ / ₄ " x 37 ³ / ₈ "	74 lbs.
H45R	5 gang, 400 Amp main, 200 Amp per position	5	22 ³ / ₄ " x 6 ¹ / ₄ " x 46 ³ / ₄ "	87 lbs.
H46R	6 gang, 400 Amp main, 200 Amp per position	6	22 ³ / ₄ " x 6 ¹ / ₄ " x 56 ¹ / ₈ "	104 lbs.

- Double entrance holes (top)
- Factory bussed 400 Amp Mains
- 200 Amp, 600 VOLT per position
- 2 - 6 position horizontal
- 4 Jaw meter sockets
- CSA weatherproof enclosure 3
- Approved conductor range:
Line 1 - No. 2 - 600 MCM CU/AL
or Two - 1/0 - 250 MCM CU/AL
Load No. 6 - 250 MCM CU/AL

- For overhead order "HD" Series hub separate
- Add suffix "H" for right hand entry, contact sales office for cost
- Approved for overhead installations only
- Use SXX503 for 5th jaw at 9 O'clock
- Use SXC022 for water heater lug kit

KNOCKOUT CODE	CONDUIT SIZE
G	1 ¹ / ₄ ", 1 ¹ / ₂ ", 2", 2 ¹ / ₂ "
S	3", 3 ¹ / ₂ ", 4"
AA	1 ¹ / ₂ "

