

ORF-P 120V Preassembled Constant Wattage Heating Cable for Pipes



Features

Nominal voltage

- 120V.

Linear density

- 7 Watts per foot.

Cold lead length

- 30 in. (0.76 m).

Outer jacket

- PVC.

Bus wire

- Nickel plated copper.

Minimum bend radius

- 5/16 in. (8 mm).

Included hardware

- Built-in bi-metal thermostat energizes the cable when temperature falls below 4 °C (40 °F).
- Grounded 3-pronged plug with indicator light to show when the cable is on.

Installation

- **Never cut or shorten the heating cable.**
- Installation under the insulation of the pipe
- For indoor and outdoor applications.
- Minimum installation temperature: 0 °C (34 °F).

Warranty

- 1-year basic warranty on the heating cable.

Application

- Metallic and non-metallic pipes.
- Helps to prevent damage caused by frozen pipes.

Models

Product # ¹	Price	Length		Watts
		ft.	m	
ORF-P003	30.00	3	0.9	21
ORF-P006	32.00	6	1.8	42
ORF-P009	38.00	9	2.7	63
ORF-P012	39.00	12	3.7	84
ORF-P015	40.00	15	4.6	105
ORF-P018	44.00	18	5.5	126
ORF-P024	56.00	24	7.3	168
ORF-P030	60.00	30	9.0	210
ORF-P040	82.00	40	12.2	280
ORF-P060	104.00	60	18.3	420
ORF-P080	125.00	80	24.4	560

¹ Must be plugged into a 120V outlet fitted with ground fault protection device (GFCI).

Options

Product # Kit	Price	Description
ELB-02B	59.00	Self-adhesive glass fiber tape, max. temp. = 90 °C (194 °F), 50 m (165 ft.)
ELB-06C	45.00	Self-adhesive aluminum tape, max. temp. = 80 °C (176 °F), 50 m (165 ft.)