

www.votatec.ca





















## Features:

- Isolated Driver
- Flicker Free
- 15.7"(40cm) Cable

Specification		
	Single CCT	5Way CCT adjustable
Model No.	VO-RP4W9-120-30-D VO-RP4W9-120-40-D VO-RP4W9-120-50-D VO-RP4W9-120-60-D	VO-RP4W9-120-D-5WAY WH
Size	4.92"x0.8" (Lamp) 3.98"X2.8"X1.38" (Driver)	
Beam Angle	120°	
Input	120V 60Hz	
Power Factor	>0.9	
Dimmable	Yes	
Power (W )	9 W	
Luminous Flux	750LM	
Color Temperature	3000K/4000K/5000K/6000k	2700K/3000K/3500K/4000K/5000K adjustable
CRI	>80	
SDCM	<7	
Life Tume ( Hrs )	50000	
Certification Requirements	ETL / ES /5 Years	

www.votatec.ca

## **Features**

- Safe - This downlight is IC Rated and airtight junction box, protecting from overheating and designed to be installed in the ceiling surrounded by insulation.

It is ETL certified, which means it has met the nationality recognized safety requirements.

- Energy Efficient With Energy Star labled, it consumes only 9 watts, equivalent to 60W halogen. That's so easy to save up to %90 on the electric bill.
- Long Lifespan The lifespan is as long as 50/000 hours. we provide 5 years warranty and lifetime technical support.





















