

CTS Series

20 AMP - 600 VOLTS c/w Test Switch Comp.



| CATALOGUE # | DESCRIPTION | WEIGHT |
|-------------|---|---------|
| CTS400PW | 4 Jaw | 24 lbs. |
| CTS500PW | 5 Jaw - 5th Jaw in 6 O'clock position | 24 lbs. |
| CTS405PW | 5 Jaw - for 4th Jaw application*, 5th Jaw at 9 O'Clock position | 24 lbs. |
| CTS800PW | 8 Jaw | 26 lbs. |
| CTS130PW | 13 Jaw | 26 lbs. |
| CTS139PW | 13 JAW - with by-pass | 26 lbs. |
| CTS130PW-TS | 13 JAW c/w 10 pole test switch | 30 lbs. |
| CTS400PW-TS | 4 JAW -c/w 4 pole test switch | 30 lbs. |

- Transformer rated for services over 200 Amps
- CSA enclosure 3
- CSA approved for copper only
- Conductor range for No. 14 - No. 8 CU
- Meter socket with compartment for test switches or test blocks
- Bottom cover is lockable and sealable

| KNOCKOUT CODE | CONDUIT SIZE |
|---------------|------------------|
| N | 3/4", 1", 1 1/4" |

