

# CTS Series



METER  
SOCKETS

## 20 AMP - 600 VOLTS c/w Compartment for Test Switch

CATALOGUE #	TYPE	DESCRIPTION	DIMENSIONS (IN.)			WEIGHT
			H	W	D	
CTS400PW	U/G	4 Jaw	20	12	4 <sup>3</sup> / <sub>4</sub>	24 lbs.
CTS500PW	U/G	5 Jaw - 5th Jaw in 6 O'clock position	20	12	4 <sup>3</sup> / <sub>4</sub>	24 lbs.
CTS405PW	U/G	5 Jaw - for 4th Jaw application, 5th Jaw at 9 O'Clock position	20	12	4 <sup>3</sup> / <sub>4</sub>	24 lbs.
CTS800PW	U/G	8 Jaw	20	12	4 <sup>3</sup> / <sub>4</sub>	26 lbs.
CTS130PW	U/G	13 Jaw	20	12	4 <sup>3</sup> / <sub>4</sub>	26 lbs.
CTS139PW	U/G	13 Jaw - with by-pass	20	12	4 <sup>3</sup> / <sub>4</sub>	26 lbs.

- Transformer rated for services over 200 Amps
- CSA enclosure 3R
- CSA approved for copper only
- Conductor range for No. 14 - No. 8 CU
- Meter socket with compartment for test switches or test blocks
- Bottom cover is lockable and sealable

Suffix:  
- BC for British Columbia  
- NS for Nova Scotia

KNOCKOUT CODE	CONDUIT SIZE
N	3/4", 1", 1 1/4"

