



EK Series

200 AMP - 600 VOLTS Oversize Enclosure

CATALOGUE #	TYPE	DESCRIPTION	KO TYPE	DIMENSIONS (IN.)			WEIGHT
				H	W	D	
EK400RO	O/H & U/G	4 Jaw, oversize enclosure	F	18	12	4 ³ / ₄	15 lbs.
E400RO	O/H & U/G	4 Jaw, straight lugs on line side	F	18	12	4 ³ / ₄	15 lbs.
EK400TO	U/G	4 Jaw, underground oversize enclosure	F	18	12	4 ³ / ₄	15 lbs.
EK400ROBC	O/H & U/G	4 Jaw, c/w 3" KO in bottom	E	18	12	5 ¹ / ₈	15 lbs.
EK200XL	O/H & U/G	4 Jaw, 350MCM type connectors on line side	E	22 ¹ / ₄	16 ¹ / ₂	4 ³ / ₄	22 lbs.
EK200XLD	O/H & U/G	4 Jaw, 350MCM type connectors on line side, 4-1/2" in top hub opening	E	22 ¹ / ₄	16 ¹ / ₂	4 ³ / ₄	22 lbs.

- CSA enclosure 3R
- Barrel type connectors angled at 45°
- Conductor range No. 6 -250 MCM CU/AL
- Lay-in neutral (can be used with unbroken neutral wire)
- Add suffix NS for ground lug on neutral for New Brunswick only

- Field adaptable accessories
- 5th Jaw at 9 O'clock **SXK503**
- 5th Jaw at 6 O'clock **INK501**
- Insulated neutral **INK200**

KNOCKOUT CODE	CONDUIT SIZE
AA	1/2"
G	1 ¹ / ₄ ", 1 ¹ / ₂ ", 2", 2 ¹ / ₂ "
F	1", 1 ¹ / ₄ ", 1 ¹ / ₂ ", 2", 2 ¹ / ₂ ", 3"

