

EK Series

200 AMP - 600 VOLTS Standard Enclosure



METER
SOCKETS

CATALOGUE #	TYPE	DESCRIPTION	KO TYPE	DIMENSIONS (IN.)			WEIGHT
				H	W	D	
EK400P	O/H & U/G	4 Jaw c/w hub plate	A	15	8 ⁵ / ₈	4 ³ / ₄	12 lbs.
EK400L	O/H & U/G	4 Jaw c/w 2" hub	A	15	8 ⁵ / ₈	4 ³ / ₄	12 lbs.
EK400D	O/H & U/G	4 Jaw c/w 2 - 2" hub	A	15	8 ⁵ / ₈	4 ³ / ₄	12 lbs.
EK400DP	O/H & U/G	4 Jaw c/w 2 - 2" hub plates, twin opening	A	15	8 ⁵ / ₈	4 ³ / ₄	12 lbs.
EK400T	U/G	4 Jaw, underground	B	15	8 ⁵ / ₈	4 ³ / ₄	12 lbs.

- CSA enclosure 3R
- Barrel type connectors angled at 45°
- Conductor range No. 6 -250 MCM CU/AL
- Lay-in neutral (can be used with unbroken neutral wire)
- Add suffix "NS" for ground lug on neutral for New Brunswick only.
PART # ZMS07051433 Ground Neutral Assembly

- Field adaptable accessories
- 5th Jaw at 9 O'clock **SXK503**
- 5th Jaw at 6 O'clock **INK501**
- Insulated neutral **INK200**

KNOCKOUT CODE	CONDUIT SIZE
AA	1/2"
G	1 1/4", 1 1/2", 2", 2 1/2"
F	1", 1 1/4", 1 1/2", 2", 2 1/2", 3"

