

H20 Series



200 AMP - MULTI POSITION 200 Amp Main

CATALOGUE #	TYPE	DESCRIPTION	DIMENSIONS (IN.)			WEIGHT
			H	W	D	
H22R	O/H & U/G	2 gang, 200 Amp main, 200 Amp per position	15 ¹ / ₈	17 ⁷ / ₁₆	5 ¹ / ₈	42 lbs.
H23R	O/H & U/G	3 gang, 200 Amp main, 200 Amp per position	15 ¹ / ₈	26 ³ / ₁₆	5 ¹ / ₈	58 lbs.
H24R	O/H & U/G	4 gang, 200 Amp main, 200Amp per position	15 ¹ / ₈	34 ¹⁵ / ₁₆	5 ¹ / ₈	74 lbs.

- Factory Bussed - 200 Amp Mains
- 4 Jaw meter socket
- 200 Amp - 600 Volts per position
- CSA enclosure 3R
- Approved conductor range:
Line 6-250 MCM AWG CU/AL
Load No. 6-250 MCM AWG

- Order **SXC** hubs separate
- Approved for overhead or underground use
- Add suffix "H" for right hand entry

KNOCKOUT CODE	CONDUIT SIZE
G	1 ¹ / ₄ " , 1 ¹ / ₂ " , 2" , 2 ¹ / ₂ "
AA	1 ¹ / ₂ "
F	1 ¹ / ₄ " , 1 ¹ / ₂ " , 2" , 2 ¹ / ₂ " , 3"

