SDC Series



100 AMP - MULTI POSITION 200 Amp Mains c/w Blank Compartment

CATALOGUE #	DESCRIPTION	METER POSITIONS	ENCLOSURE SIZE A X B X C	WEIGHT
SDC220PW	c/w blank compartment on left side - 2 gang	2	22 ¹ /2" x 12" x 5"	24 lbs.
SDC320PW	c/w blank compartment on left side - 3 gang	3	30" x 12" x 5"	32 lbs.
SDC420PW	c/w blank compartment on left side - 4 gang	4	$37^{1}/_{2}$ " x 12" x 5"	40 lbs.
SDC520PW	As Above - 5 gang	5	45" x 12" x 5"	47 lbs.
SDC620PW	As Above - 6 gang	6	52" x 12" x 5"	56 lbs.
SDC220PWBC	1 - 3" KO in bottom	2	26 ¹ / ₄ " x 15" x 5"	32 lbs.

- Factory Bussed 200 Amp mains
- 2 4 position horizontal
- 4 Jaw meter sockets
- 100 Amp 600 VOLTS per position
- All units above c/w 3" KO for BC
- Approved conductor range: Line No. 6-250 MCM CU/AL Load No. 6-1/0 AWG CU/AL
- Approved for overhead or underground use

- Field adaptable accessories
- 5th Jaw at 9 O'clock SXK503
- For overhead "SXC" hub
- Add "RH" if right hand entry required, contact Sales Office for pricing

KNOCKOUT CODE	CONDUIT SIZE		
D	11/4", 11/2", 2"		
F	1, 11/4", 11/2", 2", 21/2", 3"		
AA	1/2"		





