

# SFC Series



## 100 AMP - 7 JAW Polyphase 3 PH - 4 Wire Meter Sockets

CATALOGUE #	DESCRIPTION	ENCLOSURE SIZE H X W X D	WEIGHT
<b>SFC700PW</b>	7 Jaw overhead c/w hub closure plate	15 <sup>3</sup> / <sub>8</sub> " x 8 <sup>5</sup> / <sub>8</sub> " x 5"	12 lbs.
<b>SFC703PW</b>	as above, c/w insulated neutral	15 <sup>3</sup> / <sub>8</sub> " x 8 <sup>5</sup> / <sub>8</sub> " x 5"	12 lbs.
<b>SFC800PW</b>	8 Jaw - overhead	15 <sup>3</sup> / <sub>8</sub> " x 8 <sup>5</sup> / <sub>8</sub> " x 5"	12 lbs.
<b>SFC700RW</b>	7 Jaw combination overhead/underground	15 <sup>3</sup> / <sub>8</sub> " x 8 <sup>5</sup> / <sub>8</sub> " x 5"	12 lbs.

- 100 Amp, 600 VOLT
- CSA enclosure 3
- CSA approved for copper or aluminum
- Conductor range #6 - 1/0 AWG CU/AL

- Order "SXC" hubs separately
- Insulated neutral can be field added  
**"INK 100"**

KNOCKOUT CODE	CONDUIT SIZE
<b>AA</b>	1/2"
<b>G</b>	1 <sup>1</sup> / <sub>4</sub> ", 1 <sup>1</sup> / <sub>2</sub> ", 2", 2 <sup>1</sup> / <sub>2</sub> "

