



# Grounding

## COPPER CLAD RODS

### Copper Clad Ground Rods And Connectors

Rods are bundled in bundles of 5, connectors packaged in packages of 20.

Cat. No.	Size	Wt.-lbs./ C
5806CC	5/8 x 6'	580
5808CC	5/8 x 8'	640
5810CC	5/8 x 10'	800
3406CC	3/4 x 6'	720
3408CC	3/4 x 8'	960
3409CC	3/4 x 9'	1,080
3410CC	3/4 x 10'	1,200
1010CC	1 x 10'	2,130
<b>Sectional Copper Clad Rods</b>		
5808SC	5/8 x 8'	640
5810SC	5/8 x 10'	800
3408SC	3/4 x 8'	960
3410SC	3/4 x 10'	1,200
<b>Couplings</b>		
12SC	1/2"	15
58SC	5/8"	26
34SC	3/4"	42
10SC	1"	85
<b>Driving Studs</b>		
12DS	1/2"	15
58DS	5/8"	23
34DS	3/4"	35
10DS	1"	81

Sectional copper clad rods are threaded at top and bottom. Two or more rods may be coupled together to make up the desired length. Threaded couplings are made of bronze.

Driving studs are made of high strength carbon steel and are used to prevent damage to top-end threads or couplings- 1 stud required every 2 rods.



58SC



34DS