

Volumetric Troffer



Volumetric Troffer

AVAILABLE MODELS (ALL MODELS ARE CONROLS READY)

ORDER CODE	ITEM #	SIZE	WATTS*	CCT**	LUMENS	EFFICACY (Im/W)	VOLTAGE	TRADITIONAL WATTAGE EQUIVALENT	DLC ID#
1x4									
13792	VL1-14PS35-FCCT-H	1x4	35/30/22W	3500/4000/5000K	4900/4200/3080 lm	140 lm/W	120-347VAC	3x 17WT8, 2U31T8 Fluorescent	Pending
2x2									
13794	VL1-22PS35-FCCT-H	2x2	35/30/22W	3500/4000/5000K	4900/4200/3080 lm	140 lm/W	120-347VAC	3x 17WT8, 2U31T8 Fluorescent	Pending
2x4									
13796	VL1-24PS45-FCCT-H	2x4	45/35/26W	3500/4000/5000K	6300/4900/3640 lm	140 lm/W	120-347VAC	2x 32T8, 3x 32T8 Fluorescent	Pending
13797	VL1-24PS45-FCCT-U	2x4	45/35/22W	3500/4000/5000K	6300/4900/3640 lm	140 lm/W	120-277VAC	2x 32T8, 3x 32T8 Fluorescent	Pending
13798	VL1-24PS90-FCCT-H	2x4	90/75/65W	3500/4000/5000K	12,600/10,500/9100 lm	140 lm/W	120-347VAC	6x T8, 4x T5 Fluores- cent	Pending

^{*} All power-selectable fixtures ship at the highest wattage setting

CONTROLS & SENSORS: FIELD OR FACTORY INSTALLED

ORDER CODE	ITEM #	DESCRIPTION		
	IE CONTROLS			
PIR SENSORS				
13697	SENA-SHPR	Stand-alone PIR Motion Sensor, 12-24V, 1/2" Button Snap-in, 0-10V, Daylight Harvesting, 8-12ft, Parameters set by SEN5A-ACT.	M14	

REMOTES FOR COMMISSIONING STANDALONE CONTROLS				
	13344		Commissioning Tool for SEN5A, BAY-E-SEN/PIR, BAY-E-SEN/M, and MS2-DPX-3 (Backward compatible with SEN5A/CT and RC-100)	

NETWORK	ED LIGHTING CONTROLS (NLC)	
SENSOR A	ND CONTROLLER		
13245	SENA-WHPA	BLE PIR Motion sensor, 12-24V,1/2" Button Snap-in, 0-10V, Daylight Harvesting, 8-12ft, Parameters set by Silvair App	M21
13359	SENA-WCPA	BLE PIR Motion sensor, 12-24V, Ceiling Mount, 0-10V, Daylight Harvesting, 12ft, OD3.3" WhiteTrim (ID2.7"), Parameters set by Silvair App	
WALL OR V	VIRELESS CONTROLLERS		
12654	ESRPB-W-EO	BLE Easyfit by EnOcean wireless self-powered kinetic Single rocker pad, white, wall plate included.	
12655	EDRPB-W-EO	BLE Easyfit by EnOcean wireless self-powered kinetic Double rocker pad, white, wall plate included.	
12635	PSC-DM-WS-100-BLE-SR	BLE TruBlu 120-277V, Single Gang Single Button Wall Controller, White, Parameters set by Silvair App.	
12636	PSC-DM-I-WS-100-BLE-SR	BLE TruBlu PIR Occupancy/ Vacancy Sensor, 120-277V, Single Gang Wall Controller, White, Parameters set by Silvair App.	
12637	PSC-DM-WS-400-BLE-SR	BLE TruBlu 120-277V, Single Gang 4-Button Wall Controller, White, Parameters set by Silvair App.	

VL1

Volumetric Troffer

ACCESSORIES

FACTORY MODS

CONTROLS READY

EASILY ADD CONTROLS

ANY TIME WITHOUT THE

RECESSED AND SURFACE MOUNT KIT

CUSTOM CORDS

A1xx: 300V 18/3 armored cable up to 99ft A2xx: 600V 18/3 armored cable,up to 99'

BATTERY BACKUPS

EB08*: 8W External Battery Backup, 100-347V EB18*: 18W External Battery Backup, 100-347V EB40*: 40W External Battery

Backup, 100-347V

CONTROLS

M14: Stand-alone PIR Motion Sensor, 8-12ft M21: Bluetooth NLC PIR Motion sensor, 8-12ft

NEED FOR ANY WIRING STANDALONE



CONTROLS Compatible with EiKO's Standalone



NETWORKED LIGHTING CONTROLS

Compatible with EiKO's Networked Lighting Controls System.



























SENA-SHPR

Stand-alone PIR Sensor - Snap-in

COMMISSIONING TOOL



SEN5A-ACT Commissioning tool for standalone controls







SENA-WHPA

BLE PIR Motion Sensor w/ fixture controller - Snap-in

COMMISSIONING APP (iOS)



FREE APP POWERED BY SIVAIR

iOS Device Sold Separately









FIG 3



FIG 4



^{**} All CCT-selectable fixtures ship at 4000K

^{*} Battery is wired, not secured to fixture



VL1 Volumetric Troffer

THE GO TO TROFFER SOLUTION!



Call your local sales rep for more details!



PRICE & AVAILABLITY
ON OUR WEBSITE FOR OUR
AGENT AND DISTRIBUTOR
PARTNERS



SCAN

World Headquarters, USA: 18000 W. 105th Street, 3rd Floor Olathe, KS 66061 1.800.852.2217

