

LANDSCAPE LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Landscape accent luminaire. Simple to retrofit existing line voltage systems or coordinate well with a new commercial landscape installation.

27⁄8" 📥

61/8" _

FEATURES

- Adjustable and lockable beam angle
- Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- Includes a detachable shroud
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Detachable shroud, 6' lead wire and wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1598 Listed
- Not suitable to use with external dimmers

ORDERING NUMBER

	Color Temp	Finish
5012 Accent 120V	30 <i>3000K</i>	BKBlack on AluminumBZBronze on AluminumBBRBronze on Brass

5012-30__

Example: 5012-30BBR

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585

SPECIFICATIONS Input: 110V - 120VAC

Power:	3.5W to 14.5W			
Brightness:	100 lm to 900 lm			
Beam Angle:	15° to 60°			
CRI:	85			
Rated Life:	45,000 hours			

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JUN 07 2018

ACCENT 120V 5012

/AC

LANDSCAPE LIGHTING

Accessories

Fax

Power Stake	9000-RT9-BK		Black		<i>Easy wiring accessory designed for 120V products Eliminates the need for a separate junction box</i>
Accent Snoot	5010-SNOOT-BK 5010-SNOOT-BZ 5010-SNOOT-BBR		Black on Aluminum Bronze on Aluminum Bronze on Brass		Shields lamp and reduces glare
6" Long Shroud	5010-LSHR-BK 5010-LSHR-BZ 5010-LSHR-BBR		Black on Aluminum Bronze on Aluminum Bronze on Brass		Reduce glare. Ideal for downlighting application
Gutter Mount Bracket	5000-GM-BZ		Stainless Steel		Stainless Steel universal mounting bracket for gutter mounting fixture
Tree Mount Junction Box	5000-TCP-BZ		Bronze on Aluminum		Bronze on Aluminum box with Stainless steel mounting screws. Two ½" NPT threaded holes
Optics	LENS-20-AMB Am LENS-20-GRN Great LENS-20-RED Red	en L	LENS-20-BLU LENS-20-FR LENS-20-SPR	Blue Frosted Spread	Enhances saturation of florals and foliage
Extension Rods	5000-X04-BZ4 in5000-X08-BZ8 in5000-X12-BZ12 in	5	5000-X18-BZ 5000-X24-BZ	18 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler	5000-LCO-BZ	E	Bronze		

Magnetic Transformers Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories . 0. 9075-TRN-SS 9150-TRN-SS 9300-TRN-SS 9600-TRN-SS 150W Max 300W Max 600W Max 75W Max waclighting.com Headquarters/Eastern Distribution Center **Central Distribution Center** Western Distribution Center Phone (800) 526.2588 44 Harbor Park Drive 1600 Distribution Ct 1750 Archibald Avenue Port Washington, NY 11050 Ontario, CA 91760 (800) 526.2585 Lithia Springs, GA 30122

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JUN 07 2018