

PowerPacT H-Frame 100% Rated 150 A Unit-Mount Thermal-Magnetic Circuit Breakers (600 Vac, 250 Vdc) with Factory-Sealed Trip Unit (Suitable for Reverse Connection) (Continued)

Current Rating at 104°F (40°C) ⁵¹	Fixed AC Magnetic Trip		Interrupting Rating			
	Hold	Trip	D	G	J ⁵²	L ⁵²
110 A	900 A	1700 A	HDL36110C	HGL36110C	HJL36110C	HLL36110C
125 A	900 A	1700 A	HDL36125C	HGL36125C	HJL36125C	HLL36125C
150 A	900 A	1700 A	HDL36150C	HGL36150C	HJL36150C	HLL36150C

PowerPacT J-Frame Standard (80%) Rated 250 A Unit-Mount Thermal-Magnetic Circuit Breakers with Factory-Sealed Trip Unit (Suitable for Reverse Connection)

Current Rating at 104°F (40°C)	Adjustable AC Magnetic Trip		Interrupting Rating				
	Hold	Trip	D	G	J ⁵²	L ⁵²	R ⁵²
J-Frame, 250 A, Two-Pole, 600 Vac 50/60 Hz, 250 Vdc							
150 A ⁵³	750 A	1500 A	JDL26150	JGL26150	JJL26150	JLL26150	—
175 A ⁵³	875 A	1750 A	JDL26175	JGL26175	JJL26175	JLL26175	—
200 A ⁵⁴	1000 A	2000 A	JDL26200	JGL26200	JJL26200	JLL26200	—
225 A ⁵⁴	1125 A	2250 A	JDL26225	JGL26225	JJL26225	JLL26225	—
250 A ⁵⁴	1250 A	2500 A	JDL26250	JGL26250	JJL26250	JLL26250	—
J-Frame, 250 A, Three-Pole, 600 Vac 50/60 Hz, 250 Vdc							
150 A ⁵³	750 A	1500 A	JDL36150	JGL36150	JJL36150	JLL36150	JRL36150
175 A ⁵³	875 A	1750 A	JDL36175	JGL36175	JJL36175	JLL36175	JRL36175
200 A ⁵⁴	1000 A	2000 A	JDL36200	JGL36200	JJL36200	JLL36200	JRL36200
225 A ⁵⁴	1125 A	2250 A	JDL36225	JGL36225	JJL36225	JLL36225	JRL36225
250 A ⁵⁴	1250 A	2500 A	JDL36250	JGL36250	JJL36250	JLL36250	JRL36250

PowerPacT J-Frame 100% Rated 250 A Unit-Mount Thermal-Magnetic Circuit Breakers with Factory-Sealed Trip Unit (Suitable for Reverse Connection)

Current Rating at 104°F (40°C)	Adjustable AC Magnetic Trip		Interrupting Rating				
	Hold	Trip	D	G	J ⁵²	L ⁵²	R ⁵²
J-Frame, 250 A, Two-Pole, 600 Vac 50/60 Hz, 250 Vdc							
150 A ⁵³	750 A	1500 A	JDL26150C	JGL26150C	JJL26150C	JLL26150C	—
175 A ⁵³	875 A	1750 A	JDL26175C	JGL26175C	JJL26175C	JLL26175C	—
200 A ⁵⁴	1000 A	2000 A	JDL26200C	JGL26200C	JJL26200C	JLL26200C	—
225 A ⁵⁴	1125 A	2250 A	JDL26225C	JGL26225C	JJL26225C	JLL26225C	—
250 A ⁵⁴	1250 A	2500 A	JDL26250C	JGL26250C	JJL26250C	JLL26250C	—
J-Frame, 250 A, Three-Pole, 600 Vac 50/60 Hz, 250 Vdc							
150 A ⁵³	750 A	1500 A	JDL36150C	JGL36150C	JJL36150C	JLL36150C	JRL36150C
175 A ⁵³	875 A	1750 A	JDL36175C	JGL36175C	JJL36175C	JLL36175C	JRL36175C
200 A ⁵⁴	1000 A	2000 A	JDL36200C	JGL36200C	JJL36200C	JLL36200C	JRL36200C
225 A ⁵⁴	1125 A	2250 A	JDL36225C	JGL36225C	JJL36225C	JLL36225C	JRL36225C
250 A ⁵⁴	1250 A	2500 A	JDL36250C	JGL36250C	JJL36250C	JLL36250C	JRL36250C

51. Standard lug kit: AL150HD, Terminal wire range: 14–3/0 AWG Al or Cu.

52. UL Listed/CSA Certified as current-limiting circuit breakers.

53. Standard lug kit: AL175JD, Terminal wire range: 4–4/0 AWG Al or Cu.

54. Standard lug kit: AL250JD, Terminal wire range: 3/0 AWG–350 kcmil Al or Cu.