

Service Entrance Devices

Table 75 - Residential Enclosed Circuit Breaker with PowerPacT Q-Frame Molded Case Circuit Breakers



QO2150MRBE

| Enclosure | Mains Rating | Short Circuit Rating | General Purpose | Included In Package |
|-------------------|--------------|----------------------|--------------------------|--|
| Rainproof NEMA 3R | 150 A | 25 kA | QO2150MRBE | Factory Installed: (1) QDL22150 (1) Service entrance barrier (1) Emergency disconnect label & (1) Service disconnect label |
| Rainproof NEMA 3R | 200 A | 25 kA | QO2200MRBE | Factory Installed: (1) QDL22200 (1) Service entrance barrier (1) Emergency disconnect label & (1) Service disconnect label |
| Rainproof NEMA 3R | 70–200 A | 10–100 kA | QO2200RBE ¹²⁶ | Factory Installed: (1) Emergency disconnect label & (1) Service disconnect label Factory Included: (1) Service entrance barrier ¹²⁷ |

Table 76 - Replacement Kit for Residential Enclosed Circuit Breaker with PowerPacT Q-Frame Molded Case Circuit Breakers

| Mains Rating | Short Circuit Rating | Commercial Reference | Included In Package |
|--------------|----------------------|----------------------|--|
| 70–200 A | 10–100 kA | PKSB1Q2 | (1) Service entrance barrier & (1) Emergency disconnect label ¹²⁶ |

Table 77 - PowerPacT Q-Frame Molded Case Circuit Breakers for Residential



QBL22070

| Service | Type 3R — Rainproof Circuit Breaker not included | Ampere Rating | Short Circuit Rating | | | |
|--------------------|--|---------------|----------------------|----------|----------|-----------|
| | | | 10 k AIR | 25 k AIR | 65 k AIR | 100 k AIR |
| 2P 240 Vac Maximum | QO2200RBE | 70 A | QBL22070 | QDL22070 | QGL22072 | QJL22073 |
| | | 80 A | QBL22080 | QDL22080 | QGL22080 | QJL22080 |
| | | 90 A | QBL22090 | QDL22090 | QGL22090 | QJL22090 |
| | | 100 A | QBL22100 | QDL22100 | QGL22100 | QJL22100 |
| | | 110 A | QBL22110 | QDL22110 | QGL22110 | QJL22110 |
| | | 125 A | QBL22125 | QDL22125 | QGL22125 | QJL22125 |
| | | 150 A | QBL22150 | QDL22150 | QGL22150 | QJL22150 |
| | | 175 A | QBL22175 | QDL22175 | QGL22175 | QJL22175 |
| | | 200 A | QBL22200 | QDL22200 | QGL22200 | QJL22200 |

126. Suitable ONLY for breakers from 70-200 A. Not compatible with 225 A breakers.
 127. Suitable only for 2P Q-frame molded case circuit breakers only.