

TradeSelect, Straight Blade, Single Panel Mount Receptacle, 30A 125/250V, 3-Pole 4-Wire Grounding, 14-30R, Black, With Plate



By Hubbell Wiring Device-Kellems
Catalog # [RR430WIPC�](#)

TradeSelect, Straight Blade, Single Panel Mount Receptacle, 30A 125/250V, 3-Pole 4-Wire Grounding, 14-30R, Black, With Plate

Features

- Single Panel Mount Receptacle
- 30A 125/250V
- 3-Pole 4-Wire Grounding

Application

Residential Grade

General

Catalog Number	RR430WIPC�
Color	White
EU RoHS Indicator	No
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	Flanged Single
Material	Thermoplastic
Material - Mounting Hardware	Screw Mounting
Number Of Poles	3-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
UPC	883778301858

Dimensions

Display Size Standard Sized Product

Electrical Ratings

Amperage Rating	30 A
Connectivity	Screw Terminals
Current / Amperage Rating	30 A
Current Rating	30 A
Phase	Single Phase
Voltage Rating	125/250 VAC
Wattage	7500

Conductor Related

Number Of Wires	4-Wire Grounding
Wire Size	#10 AWG

Certifications And Compliance

Nema Rating	14-30R
-------------	--------

Logistics

Carton Quantity	10
-----------------	----

Product Assets

[Catalog Page - WDK Z-17 Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)
[Engineering Drawing - RR430WIPC� AutoCAD Drawing](#)
[Installation Manuals - WIRING_PD2193_INSTALLINST](#)
[Sales Drawings - WDK_RR430WIPC�_DRAWING_PDF](#)
[Specifications - RR430WIPC�](#)
[Warranty - tradeSELECT™ and netSELECT®](#)