

Series

ORF-P

120V Preassembled Constant Wattage Heating Cable for Pipes



Features

Nominal voltage
Linear density
Cold lead length
Outer jacket
Bus wire
Minimum bend radius
Included hardware

- 120V.
- 7 Watts per foot.
- 30 in. (0.76 m).
- PVC.
- Nickel plated copper.
- 5/16 in. (8 mm).
- Built-in bi-metal thermostat energizes the cable when temperature falls below 4 °C (40 °F).
- Grounded 3-pronged plug with indicator light to show when the cable is on.
- **Never cut or shorten the heating cable.**
- Installation under the insulation of the pipe.
- For indoor and outdoor applications.
- Minimum installation temperature: 0 °C (34 °F).
- **1-year basic warranty on the heating cable.**
- Metallic and non-metallic pipes.
- Helps to prevent damage caused by frozen pipes.

Installation

Warranty
Application

Models

Product # ¹	Length		Watts	Qty
	ft.	m		
ORF-P003	3	0.9	21	
ORF-P006	6	1.8	42	
ORF-P009	9	2.7	63	
ORF-P012	12	3.7	84	
ORF-P015	15	4.6	105	
ORF-P018	18	5.5	126	
ORF-P024	24	7.3	168	
ORF-P030	30	9.0	210	
ORF-P040	40	12.2	280	
ORF-P060	60	18.3	420	
ORF-P080	80	24.4	560	

¹ Must be plugged into a 120V outlet fitted with ground fault protection device (GFCI).

Options

Product # Kit	Description	Qty
ELB-02B	Self-adhesive glass fiber tape, max. temp. = 90 °C (194 °F), 50 m (165 ft.)	
ELB-06C	Self-adhesive aluminum tape, max. temp. = 80 °C (176 °F), 50 m (165 ft.)	

Specifications may change without prior notice

Project:	Approval Information
Consultant Engineer:	
Electrician Contractor:	
Distributor:	
Date:	
Contact in Ouellet:	
Comments:	