

# MSC Series



## 200 AMP - MULTI POSITION STUD TYPE 400 Amp Mains c/w Blank Wiring Comp.

CATALOGUE #	DESCRIPTION	METER POSITIONS	ENCLOSURE SIZE A X B X C	WEIGHT
<b>MSC820TW</b>	2 gang, c/w 1/2" compression studs	2	22 <sup>3</sup> / <sub>4</sub> " x 6 <sup>1</sup> / <sub>4</sub> " x 37 <sup>3</sup> / <sub>8</sub> "	53 lbs.
<b>MSC830TW</b>	3 gang, c/w 1/2" compression studs	3	22 <sup>3</sup> / <sub>4</sub> " x 6 <sup>1</sup> / <sub>4</sub> " x 46 <sup>3</sup> / <sub>4</sub> "	70 lbs.
<b>MSC840TW</b>	4 gang, c/w 1/2" compression studs	4	22 <sup>3</sup> / <sub>4</sub> " x 6 <sup>1</sup> / <sub>4</sub> " x 56 <sup>1</sup> / <sub>8</sub> "	88 lbs.
<b>MSC850TW</b>	5 gang, c/w 1/2" compression studs	5	22 <sup>3</sup> / <sub>4</sub> " x 6 <sup>1</sup> / <sub>4</sub> " x 65 <sup>1</sup> / <sub>2</sub> "	108 lbs.
<b>MSC860TW</b>	6 gang, c/w 1/2" compression studs	6	22 <sup>3</sup> / <sub>4</sub> " x 6 <sup>1</sup> / <sub>4</sub> " x 74 <sup>1</sup> / <sub>4</sub> "	126 lbs.

\* Also available with one (1) blank compartment (see MSC42TW Series)

- Factory Bussed 400 Amp Mains
- 200 Amp, 600 VOLT per position
- 2 - 6 position horizontal
- 4 Jaw meter sockets
- CSA weatherproof enclosure 3
- Approved conductor range:  
Line - studs (two 1/2" per phase) provided for compression type wire connectors  
Load - #6 - 250 MCM CU/AL
- Underground only
- Also approved in Ottawa area

Use SXX503 for 5th jaw at 9 O'clock  
Use SXC022 for water heater lug kit

KNOCKOUT CODE	CONDUIT SIZE
<b>G</b>	1 <sup>1</sup> / <sub>4</sub> ", 1 <sup>1</sup> / <sub>2</sub> ", 2", 2 <sup>1</sup> / <sub>2</sub> "
<b>S</b>	3", 3 <sup>1</sup> / <sub>2</sub> ", 4"
<b>AA</b>	1/2"

