

Project \_\_\_\_\_  
 Schedule \_\_\_\_\_ Date \_\_\_\_\_  
 Notes \_\_\_\_\_

**DESCRIPTION**

naturaLED® PAR LED bulb provides a superior replacement for all incandescent PAR lamp applications. An energy efficient integrated LED driver deliver the same lumen output equivalent with up to 78% energy savings. Our PAR lamps are direct replacement with energy star certification for wet or damp locations. Perfect for display case lighting, track lighting, jewelry lighting and general lighting.



**FEATURES**

- Energy star certified
- For damp locations
- Outdoor rated for wet locations
- Direct replacement and Instant On
- Up to 78% energy savings
- Uniform and consistent color
- Contains no mercury or lead
- UL/cUL Listed
- Input line voltage: 120V
- Operating temperature: -22°F ~ 122°F
- Beam Angle: 40°
- Rated 25,000 hours average life

**APPLICATIONS**

- Display Case Lighting
- Track Lighting
- Recessed Downlight
- Accent Lighting
- General Lighting

**WARRANTY**

- 5 Year Warranty

Ordering Information		EXAMPLE: LED15PAR38/OD/120L/FL/930				
LED	15	PAR38	OD	120L	FL	930
	<b>Wattage</b>	<b>Style</b>	<b>Style</b>	<b>Lumens</b>	<b>Beam Angle</b>	<b>CRI/Color Temp</b>
<b>LED</b>	<b>15</b> 15-Watts	<b>PAR38</b> PAR38	<b>OD</b> Outdoor	<b>120L</b> 1,200 lm	<b>FL</b> Flood	<b>9</b> CRI90 <b>30</b> 3000K <b>40</b> 4000K <b>50</b> 5000K

ORDERING

Watts (W)	Ordering Code	Description	Color Temp (K)	Lumens (lm)	Equiv. Wattage (W)	Base	CRI	Beam Angle	Rated Hrs	Damp/Wet Location	Energy Star
8	5924	LED8PAR20/50L/FL/930	3000K	500	50	E26	90	40°	25,000	Damp	•
8	5925	LED8PAR20/50L/FL/950	5000K	500	50	E26	90	40°	25,000	Damp	•
10	5926	LED10PAR30/80L/FL/930	3000K	800	75	E26	90	40°	25,000	Damp	•
10.5	5927	LED10PAR30/80L/FL/950	5000K	800	75	E26	90	40°	25,000	Damp	•
10.5	5928	LED10PAR30L/OD/80L/FL/930	3000K	800	75	E26	90	40°	25,000	Wet	•
10.5	5997	LED10PAR30L/OD/80L/FL/940	4000K	800	75	E26	90	40°	25,000	Wet	•
10.5	5929	LED10PAR30L/OD/80L/FL/950	5000K	800	75	E26	90	40°	25,000	Wet	•
15	5930	LED15PAR38/OD/120L/FL/930	3000K	1,200	100	E26	90	40°	25,000	Wet	•
15	5998	LED15PAR38/OD/120L/FL/940	4000K	1,200	100	E26	90	40°	25,000	Wet	•
15	5931	LED15PAR38/OD/120L/FL/950	5000K	1,200	100	E26	90	40°	25,000	Wet	•

SPECIFICATIONS

PAR 20	PAR 30	PAR 30L	PAR 38
Weight: 3.68-oz	Weight: 6.56-oz	Weight: 7.68-oz	Weight: 12.64-oz

PACKAGE

PAR20  
PAR30

Package (Master)  
20

PAR38

Package (Master)  
10