

## 30A and 50A Residential, Commercial and Industrial Grade Power Devices

Rating	Receptacle/Plug Configuration & NEMA No.	Flush Mount Receptacle	Surface Mount Receptacle	Panel Mount Receptacle	Angle Plug	Wallplate Size
<b>2-Pole, 3-Wire, Grounding</b>						
30A-125V	5-30R 	5-30P 	5371/5371-IG* 	—	—	9530-P 
30A-125V	TT-30R 	TT-30P 	7313 	—	—	830-T 
30A-250V	6-30R 	6-30P 	5372/5372-IG* 	5376 	—	9630-P 
30A-277V	7-30R 	7-30P 	9730-A 	—	—	9730-P 
50A-125V	5-50R 	5-50P 	5373 	—	—	9550-P 
50A-250V	6-50R 	6-50P 	5374/5374-IG* 	5378 	—	9650-P 
50A-277V	7-50R 	7-50P 	9750-A 	—	—	9750-P 

\*Isolated Ground.

**WARNING:** Do not use with single-gang wallboxes, single-gang mud rings or single-gang box extenders

*Continued on next page*

### Wallplates

#### 1-Gang

30A and 50A Receptacle,  
2.15" dia. hole



Thermoset (Plastic) 80528-W  
Thermoplastic (Nylon) 80728-W  
Stainless Steel 84028

#### 2-Gang

30A and 50A Receptacle,  
2.15" dia. hole



Thermoset (Plastic) 80526-W  
Thermoplastic (Nylon) 80726-W  
Stainless Steel 84026

See Wallplates section pages **S-9** and **S-10** for complete ordering information