





DUPLEX AND SINGLE RECEPTACLES

Duplex Receptacles, 2 Pole, 3 Wire

Description	Standard			Standard
		Weather and Tamper-Resistant	Tamper-Resistant	
Termination	Grounding, Push and Side Wire	Self-Grounding, Push and Side Wire	Self-Grounding, Push and Side Wire	Self-Grounding, Push and Side Wire
Rating	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R
Almond	RR15AL	RR15SALWRTR	RR15SALTR	RR15SAL
Black	RR15BK	RR15SBKWRTR	RR15SBKTR	RR15SBK
Brown	RR15	RR15SWRTR	RR15STR	RR15S
Ivory	RR15I	RR15SIWRTR	RR15SITR	RR15SI
Light Almond	RR15LA	RR15SLAWRTR	RR15SLATR	RR15SLA
White	RR15W	RR15SWWRTR	RR15SWTR	RR15SW






RR15W

Description		Standard, Without Ears		Standard, Without Ears**
	Tamper-Resistant, Without Ears		Tamper-Resistant, Without Ears**	
Termination	Eight Push Wire Holes Only #14 AWG	Eight Push Wire Holes Only #14 AWG	Eight Push Wire Holes Only #14 AWG	Eight Push Wire Holes Only #14 AWG
Rating	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R
Almond	RR15EALTR	RR15EAL	RR15KALTR	RR15KAL
Black	RR15EBKTR	RR15EBK	—	—
Brown	RR15ETR	RR15E	RR15KTR	RR15K
Gray	RR15EGYTR	RR15EGY	—	—
Ivory	RR15EITR	RR15EI	RR15KITR	RR15KI
Light Almond	RR15ELATR	RR15ELA	RR15KLATR	RR15KLA
White	RR15EWTR	RR15EW	RR15KWTR	RR15KW






RR15KW

Single Receptacles, 2 Pole, 3 Wire

Description			Standard		Standard
	Weather and Tamper-Resistant	Tamper-Resistant		Weather Resistant	
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 250V NEMA 6-15R	15A 250V NEMA 6-15R
Almond	RR151ALWRTR	RR151ALTR	RR151AL	RR155ALWR	RR155AL
Black	RR151BKWRTR	RR151BKTR	RR151BK	RR155BKWR	RR155BK
Brown	RR151WRTR	RR151TR	RR151	RR155WR	RR155
Gray	RR151GYWRTR	RR151GYTR	RR151GY	RR155GYWR	RR155GY
Ivory	RR151IWRTR	RR151ITR	RR151I	RR155IWR	RR155I
Light Almond	RR151LAWRTR	RR151LATR	RR151LA	RR155LAWR	RR155LA
White	RR151WWRTR	RR151WTR	RR151W	RR155WWR	RR155W



RR151W

Description			Standard		Standard
	Weather and Tamper-Resistant	Tamper-Resistant		Weather Resistant	
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	20A 125V NEMA 5-20R	20A 125V NEMA 5-20R	20A 125V NEMA 5-20R	20A 250V NEMA 6-20R	20A 250V NEMA 6-20R
Almond	RR201ALWRTR	RR201ALTR	RR201AL	RR205ALWR	RR205AL
Black	RR201BKWRTR	RR201BKTR	RR201BK	RR205BKWR	RR205BK
Brown	RR201WRTR	RR201TR	RR201	RR205WR	RR205
Gray	RR201GYWRTR	RR201GYTR	RR201GY	RR205GYWR	RR205GY
Ivory	RR201IWRTR	RR201ITR	RR201I	RR205IWR	RR205I
Light Almond	RR201LAWRTR	RR201LATR	RR201LA	RR205LAWR	RR205LA
White	RR201WWRTR	RR201WTR	RR201W	RR205WWR	RR205W



RR201W

Note: ** 100 per case, bulk packed. Mounting screws inserted into strap.

GFCI RECEPTACLES

F15

SAFETY AND ECONOMY.

 Meets UL Standard 943
Class A GFCI



GF151LA

10kA Short Circuit Current Rating

Comprehensive diagnostics

- When test button is actuated, both the electronic components and mechanical trip mechanism are functionally tested

Ground fault indicator

- Flashing **RED** indicates device has lost capability to provide protection

No power at face if reverse wired

- Open circuit condition eliminates false assumption of protection at face

Installation ease

- Internal back wiring
- Automatic grounding feature
- Captive mounting screws

tradeSELECT™

GFCI Duplex Receptacles, Flush Nylon Face, Matching Nylon Wallplate Included







GFTR20I



GF151LA



GFBF20ILA

Description	 Tamper-Resistant Weather Resistant	 Tamper-Resistant Weather Resistant	 Standard	 Standard
	15A 125V AC NEMA 5-15R	20A 125V AC NEMA 5-20R	15A 125V AC NEMA 5-15R	20A 125V AC NEMA 5-20R
Termination	Self-Grounding, Back and Side Wire	Self-Grounding, Back and Side Wire	Self-Grounding, Back and Side Wire	Self-Grounding, Back and Side Wire
Rating	15A 125V AC NEMA 5-15R	20A 125V AC NEMA 5-20R	15A 125V AC NEMA 5-15R	20A 125V AC NEMA 5-20R
Almond	GFTR15AL	GFTR20AL	GF15ALLA	GF20ALLA
Black	GFTR15BK	GFTR20BK	GF15BKLA	GF20BKLA
Brown	GFTR15	GFTR20	GF15LA	GF20LA
Gray	GFTR15GY	GFTR20GY	GF15GYLA	GF20GYLA
Ivory	GFTR15I	GFTR20I	GF15ILA	GF20ILA
Light Almond	GFTR15LA	GFTR20LA	GF15LALA	GF20LALA
Red	GFTR15R	GFTR20R	GF15RLA	GF20RLA
White	GFTR15W	GFTR20W	GF15WLA	GF20WLA

GFCI Duplex Receptacles, Flush Nylon Face, Matching Nylon Wallplate Included

Description	Circuit Guard® Faceless
Termination	Self-Grounding, Back and Side Wire
Rating	20A 125V NEMA 5-20R
Almond	GFBF20ALLA
Black	GFBF20BKLA
Brown	GFBF20LA
Gray	GFBF20GYLA
Ivory	GFBF20ILA
Light Almond	GFBF20LALA
Red	GFBF20RLA
White	GFBF20WLA

