


ACCENT 12V

5011

WAC

LANDSCAPE LIGHTING



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Landscape accent luminaire. One fixture replaces all older halogen landscape accent lights

FEATURES

- Adjustable and lockable beam angle
- Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- Includes a detachable shroud
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Mounting stake, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- MLV dimmable with remote MLV dimmers

SPECIFICATIONS

Input: 9 - 15VAC (Transformer is required)
Power: 1W to 18W / 2VA - 23VA
Brightness: 50 lm to 1090 lm
Beam Angle: 10° to 60°
CRI: 85
Rated Life: 70,000 hours

ORDERING NUMBER

| | | Color Temp | Finish |
|-------------|-------------------|-----------------|-------------------------------------|
| 5011 | <i>Accent 12V</i> | 27 2700K | BK <i>Black on Aluminum</i> |
| | | 30 3000K | BZ <i>Bronze on Aluminum</i> |
| | | 40 4000K | BBR <i>Bronze on Brass</i> |

5011-_____

Example: **5011-30BBR**

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760











ACCENT 12V

5011

WAC

LANDSCAPE LIGHTING

Accessories

| | | | | | |
|----------------------------|---|--|--|---|--|
| Accent Snoot |  | 5010-SNOOT-BK 5010-SNOOT-BZ 5010-SNOOT-BBR | Black on Aluminum Bronze on Aluminum Bronze on Brass | Shields lamp and reduces glare | |
| 6" Long Shroud |  | 5010-LSHR-BK 5010-LSHR-BZ 5010-LSHR-BBR | Black on Aluminum Bronze on Aluminum Bronze on Brass | Reduce glare. Ideal for downlighting application | |
| Additional Stake |  | 9000-ST9-BZ | Bronze | Durable PVC stake | |
| Surface Mount Flange/Stake |  | 5000-SCP-BZ 5000-SCP-BBR 5000-SCP-BK | Bronze on Aluminum Bronze on Brass Black on Aluminum | Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box | |
| Guardian Mount |  | 9000-SP9-BZ | Stainless Steel | Heavy duty stainless steel spike to position fixture Formed from a single piece of metal | |
| Gutter Mount Bracket |  | 5000-GM-BK | Stainless Steel | Stainless Steel universal mounting bracket for gutter mounting fixture | |
| Tree Mount Junction Box |  | 5000-TCP-BZ 5000-TCP-BK | Bronze on Aluminum Black on Aluminum | Bronze on Aluminum box with Stainless steel mounting screws. Two 1/2" NPT threaded holes | |
| Optics |  | LENS-20-AMB LENS-20-GRN LENS-20-RED | Amber Green Red | LENS-20-BLU Blue LENS-20-FR Frosted LENS-20-SPR Spread | Enhances saturation of florals and foliage |
| Extension Rods |  | 5000-X04-BZ 4 in 5000-X04-BK 4 in 5000-X08-BZ 8 in 5000-X08-BK 8 in 5000-X12-BZ 12 in 5000-X12-BK 12 in | | 5000-X18-BZ 18 in 5000-X18-BK 18 in 5000-X24-BZ 24 in 5000-X24-BK 24 in | Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box |
| Rod L-Coupler |  | 5000-LCO-BZ | Bronze | | |

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed
See transformer spec sheet for details and its accessories

9075-TRN-SS
75W Max

9150-TRN-SS
150W Max

9300-TRN-SS
300W Max

9600-TRN-SS
600W Max



wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760