SLIDE LED PATH LIGHT





LANDSCAPE LIGHTING





Fixture Type:	
Catalog Number:	
Project:	

PRODUCT DESCRIPTION

Sleek linear design blends seamlessly into pathways while providing soft, even illumination

SPECIFICATIONS

Location:

Input: 9-15VAC (Transformer is required)

 Power:
 3.0W / 4.5VA


 Brightness:
 Up to 95 lm

 CRI:
 90

 Rated Life:
 60,000 hours

FEATURES

- · IP66 rated, Protected against powerful water jets
- · Factory sealed water tight fixtures
- Translucent lens provides uniform light distribution
- Constant output for 9V-15V input
- Mounting stake, 6 foot lead wire, and direct burial gel filled wire nuts are included
- Recommended spacing for installation: Residential: 7 to 9ft; Commercial: 4 to 6ft
- Maintains constant lumen output against voltage drop
- UL & cUL 1838 Listed (12V)



ORDERING NUMBER

	Color Temp	Finish
6311 Small SI	de 30 3000K Pure Whit	te BZ Bronze on Aluminum

6311- BZ

Example: **6311-30BZ**



Surface Mount Flange/Stake



Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box

5000-SCP-BZBronze on Aluminum

Additional Mounting Stake



9000-ST9-BK *Durable PVC stake*



Guardian Mount

Heavy duty stainless steel spike to position fixture. Formed from a single piece of metal

9000-SP9-BZ *Stainless Steel*

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS *150W Max*

9300-TRN-SS 300W Max

9600-TRN-SS 600W Max

