WALL WASH 12V

5021



LANDSCAPE LIGHTING



Fixture Type:	
Catalog Number:	
Project:	
Location:	

9 - 15VAC (Transformer is required)

2W to 16W / 2VA - 23VA

PRODUCT DESCRIPTION

Landscape Wall Wash luminaire

FEATURES

- A uniform wide distribution wall wash from a small form factor
- · Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Mounting stake, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- Not suitable to use with external dimmers

ORDERING NUMBER

		Color Temp		Finish	
5021	Wall wash 12V	27 30	2700K 3000K	BK BZ BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass

5021-

Example: 5021-30BK

SPECIFICATIONS

Brightness: 190 lm to 980 lm **Beam Angle:** 15° upward (50° by 80°)

Rated Life: 70,000 hours

Input:

Power:

WALL WASH 12V





Accessories					
Addtional Stake	9000-ST9-BZ	9000-ST9-BZ			Durable PVC stake
Surface Mount Flange/Stake	5000-SCP-BZ 5000-SCP-BBR 5000-SCP-BK	5000-SCP-BBR		n	Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box
Guardian Mount	9000-SP9-BZ	9000-SP9-BZ			Heavy duty stainless steel spike to position fixture Formed from a single piece of metal
Tree Mount Junction Box	5000-TCP-BZ 5000-TCP-BK		Bronze on Aluminum Black on Aluminum		Bronze on Aluminum box with Stainless steel mounting screws. Two ½" NPT threaded holes
Gutter Mount Bracket	5000-GM-BZ 5000-GM-BK				Stainless Steel universal mounting bracket for gutter mounting fixture
Optics	LENS-2X4-AMB LENS-2X4-GRN LENS-2X4-RED	Amber Green Red	LENS-2X4-BLU LENS-2X4-FR LENS-2X4-SPR	Blue Frosted Spread	Enhances saturation of florals and foliage
Extension Rods	5000-X04-BZ 5000-X04-BK 5000-X08-BZ 5000-X08-BK 5000-X12-BZ 5000-X12-BK	4 in 4 in 8 in 8 in 12 in 12 in	5000-X18-BZ 5000-X18-BK 5000-X24-BZ 5000-X24-BK	18 in 18 in 24 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler	5000-LCO-BZ		Bronze		

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS 75W Max

9150-TRN-SS *150W Max*

9300-TRN-SS *300W Max*

9600-TRN-SS 600W Max

