ACCENT 12V COLOR CHANGING

5011-CCBBR



LANDSCAPE LIGHTING



PRODUCT DESCRIPTION

Landscape accent luminaire

FEATURES

- Color and brightness are controlled through ilumenight app
- Solid diecast brass
- Adjustable and lockable beam angle
- IP66 rated, Protected against high-pressure water jets
- Includes a detachable shroud
- Factory sealed water tight fixtures
- Mounting stake, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- Not suitable to use with external dimmers

ORDERING NUMBER

		Color	Color Temp		Finish		
5011	Accent 12V	сс	Color Changing	BBR BZ	Bronze on Brass Bronze on Aluminum		

5011-CC

Example: 5011-30BZ

SPECIFICATIONS

Input: 9V - 15VAC (Transformer is required)

Power: 0.5W to 14.5W / 1VA to 17VA

Brightness: up to 355lm Beam Angle: 15° to 60° CRI: 95 Rated Life: 45,000 hours

Controls: Bluetooth v4.0 - Configured with ilumenight[™] iOS App

for localized

(within 150ft line of sight) groups of 8 luminaires or less. Control detection can be adversely affected high wireless

signal interference environments.

ACCENT 12V

5011



5000-SCP-BBR 5000-SCP-BK Bronze on Brass ground mounting or surface mounts with four screen junction box Guardian Mount 9000-SP9-BZ Stainless Steel Heavy duty stainless steel spike to position fixture Formed from a single piece of metal Gutter Mount Bracket 5000-GM-BZ Stainless Steel Stainless Steel Universal mounting bracket for gut fixture								Accessories
6*Long Shroud 5010-LSHR-BZ 5010-LSHR-BBR Bronze on Aluminum Bronze on Brass Bronze Durable PVC stake Durable PVC stake Surface Mount Flange/Stake 5000-SCP-BZ 5000-SCP-BBR 5000-SCP	Shields lamp and reduces glare		Bronze on Aluminum		5010-SNOOT-BZ			Accent Snoot
Surface Mount Flange/Stake 5000-SCP-BBR 500	ntion	Reduce glare. Ideal for downlighting application	Bronze on Aluminum		ł	5010-LSHR-BZ		6" Long Shroud
Source Mount Flange/Stake 5000-SCP-BBR 5000		Durable PVC stake	Bronze			9000-ST9-BZ	-	Additional Stake
Gutter Mount Bracket 5000-GM-BZ 5000-GM-BK Stainless Steel Stainless Steel universal mounting bracket for gut fixture Tree Mount Junction Box 5000-TCP-BZ Bronze on Aluminum Bronze on Aluminum Two ½" NPT threaded holes LENS-20-AMB Amber LENS-20-BLU Blue LENS-20-GRN Green LENS-20-FR Frosted LENS-20-FR Spread 5000-X04-BZ 4 in 5000-X18-BZ 18 in 5000-X18-BZ 18 in 5000-X18-BZ 18 in 5000-X08-BZ 8 in 5000-X08-BK 8 in 5000-X24-BZ 24 in 5000-X		Includes three 7 inch threaded stainless steel stabiliz ground mounting or surface mounts with four screy junction box	Bronze on Brass			5000-SCP-BBR		
Tree Mount Junction Box Source on Aluminum Bronze on Aluminum Bronze on Aluminum Bronze on Aluminum Two ½" NPT threaded holes Lens-20-AMB Amber Lens-20-BLU Blue Lens-20-GRN Green Lens-20-FR Frosted Lens-20-FR Enhances saturation of florals and foliage Extension Rods Source on Aluminum Bronze on Aluminum Bronze on Aluminum Dronze on Aluminum	xture		Stainless Steel			9000-SP9-BZ		Guardian Mount
Junction Box Source Sourc	or gutter mounting	Stainless Steel universal mounting bracket for gutte fixture	Stainless Steel					
LENS-20-GRN LENS-20-FR Red LENS-20-FR Spread 5000-X04-BZ 4 in 5000-X18-BZ 18 in 5000-X18-BK 18 in 5000-X08-BZ 8 in 5000-X08-BK 8 in 5000-X08-BK 8 in 5000-X12-BZ 12 in Extension Rods Enhances saturation of florals and foliage	el mounting screws.	Bronze on Aluminum box with Stainless steel mour Two ½" NPT threaded holes						
Extension Rods 5000-X04-BZ 4 in 5000-X18-BK 18 in 5000-X24-BZ 24 in 5000-X24-BZ 24 in 5000-X24-BK 24		Enhances saturation of florals and foliage	Frosted	LENS-20-FR	Green	LENS-20-GRN		Optics
	t box		18 in 24 in	5000-X18-BK 5000-X24-BZ	4 in 8 in 8 in 12 in	5000-X04-BK 5000-X08-BZ 5000-X08-BK 5000-X12-BZ		Extension Rods
Rod L-Coupler 5000-LCO-BZ Bronze				Bronze		5000-LCO-BZ	•	Rod L-Coupler

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS *150W Max*

9300-TRN-SS *300W Max*

9600-TRN-SS 600W Max

