

First Alert®

10 Year Life SMOKE ALARM

SA3210A



10-Year LITHIUM POWER CELL

No costly battery replacement for the 10-year life of the alarm

TAMPER PROOF SEALED ALARM

Powercell cannot be removed

PHOTO / ION SENSORS

Dual Photoelectric & Ionization sensing technologies for optimal sensing of smoke particles produced in both flaming and smoldering fires

ALARM STATUS LED INDICATOR

END-OF-LIFE SIGNAL

TEST / SILENCE BUTTON

TAMPER RESISTANT

Locks alarm to mounting bracket. Perfect for apartment, dormitory or hotel applications

10 YEAR WARRANTY



IONIZATION



PHOTOELECTRIC

TECHNICAL SPECS:

Alarm Dimensions:	2" x 5" x 5"
Colour:	White
Weight:	8.4 oz
Operating Voltage:	3V Lithium Power Cell
Temperature Range:	4° C to 38° C
Humidity Range:	10% to 95% relative humidity (RH)
Audio Alarm:	85dB at 10 ft
Test / Silence:	Electronically simulates smoke condition, causing the unit to alarm. Press and hold test / silence button.
Alarm Reset:	Automatic when smoke clears
Smoke Sensors:	Photoelectric & Ionization
Listing:	Listed to UL217 Standard

SHIPPING SPECS:

Individual Clam Dimensions	6.87"W x 2.5"D x 8.5"H
Weight	.66 lbs.
Cube	0.08 ft3
UPC	029054015822
Master Carton Dimensions	7.75"L x 7.13"W x 9.00"H
Master Pack	3
Weight	2.34
Cube	0.29 ft3
Case UPC	60029054015824
Cases per Layer:	30
Number of layers:	5
Cases per Pallet:	150
Units per Pallet:	450
Cube:	54 ft3
Weight:	416 lbs